

RTV Gasket Maker

Specially designed for dealership warranty requirements that ensure extended drivetrain warranty compliance. It features fast-curing, sensor-safe, low odor, and non-corrosive formulation that meets performance specs of OE silicone gaskets. It forms reliable "formed-in-place" gaskets that resist cracking and shrinkage caused by thermal cycling. It is permanently flexible and stable between -80 °F to 600 °F (-62 °C to 315 °C). It is also resistant against automotive fluids.

Applications:

Rear valve covers, oil pans, timing covers, water pumps, thermostat housing, transmission pans, etc.

Available colour: Black

Item Code	Content	Inner Box	Carton Quantity
VT-157P85	85 g Tube Carded	12	144 / Carton
VT-157P100	100 g Tube Carded	12	144 / Carton

Vital Black Pr RTV Temp. 600 °F OEM Material Silisone Gasket Ma • For dealership warrar requirements • Fast curing formula • Low odor and non-cc Silisone Gasket Ma • For dealership warrar requirements • Fast curing formula • Low odor and non-cc Silisone Gasket Ma • For dealership warranty requirements • Fast curing formula • Low odor and non-corrosive



Features

- For dealership warranty requirements
- Fast curing formula
- Sensor-safe
- Low odor and non-corrosive







VALVE COVER



VITAL TECHNICAL SDN. BHD. (No.: 589221-K)

No, 93, Jalan Industri 3/3, Rawang Integrated Industrial Park, 48000 Rawang, Selangor Darul Ehsan, Malaysia.



) 🔛 🛭

sales@vitaltechnical.com







