

Issuance date: 27/04/17

Revision date: 24/11/20

Revision No.: 20-02

VT-2720 / VT-2721 Door Trim Tape

Principal composition:
Butyl rubber

Appearance:
Black

Odor:
None or very little

Water resistance:
Excellence

Adhesion
Good on metal, glass,
wood and concrete

PACKAGING
VT-2720
5mm x 3mm x 15m
(24 rolls / carton)

VT-2721
6mm x 8m
(24 rolls / carton)

**other sizes available upon request*

SERVICE TEMPERATURE
-20 °C to 70 °C

SHELF LIFE
18 months

STORAGE
Product is very inert and can last almost indefinitely without deteriorating.

DESCRIPTION



VT-2720 / VT-2721 Door Trim Tape is an ever-tacky, black-colored sealant with good adhesion strength. It offers a fast and clean method for sealing uneven gaps between car door trim and the main door frame.

TECHNICAL DATA	Needle penetration	: 80 – 95 (x 0.1mm, 50g / 5 secs)
	Specific gravity	: 1.10 – 1.20

FEATURES	▪ Good adhesion strength
	▪ Fast and clean method

APPLICATION	Ideal for volume car door production, where greater dimensional accuracy and lower waste are required. Shorter strips can also be used for sealing wires and electrical harnesses within the car door structure to prevent water tracking.
--------------------	--

APPLICATION DIRECTION	1. Ensure that surfaces are clean, dry, dust free, oil free and sound. 2. Release sealant from release paper and apply pressure sufficiently onto the surface for a complete contact.
------------------------------	--

CAUTION	Keep out of reach of children. Safety data sheet available on request. For further health and safety information, consult the latest safety data sheet.
----------------	---

LEGAL NOTES	Every endeavour has been made to ensure that the information given herein is true and reliable but it is given only for the guidance of our customers. The company cannot accept any responsibility for the loss or damage that may result from the use of the information, due to the possibility of variations of processing or working conditions and of workmanship outside our control. Users are advised to confirm suitability of this product by their own tests.
--------------------	---