

	VITAL TECHNICAL SDN. BHD.	 
	Technical Data Sheet	
	VT-107 Wallpaper Adhesive	

Issuance date: 07/05/2020

Revision date: -13/06/2021

Revision No.:

Product Specification:

Appearance	: Viscous liquid
Solid content	: 42.0 - 44.0%
pH	: 7.0 - 8.0
Viscosity (Brookfield LV 4, 5 rpm)	: 20,000 - 30,000 cPs
Specific gravity	: 1.15 - 1.20
Colour	: Beige
Features	: Economical : Ready mixed adhesive : Easy to apply : Easy clean up : Non-toxic
Shelf life	: 12 months

Packaging

Product Code	Content	Inner Box	Carton
VT-107125	125g bottle	12	144
VT-1071K	1kg pail	-	12



Product Description:

A ready mixed, water-based wallpaper adhesive that is excellent for all types of wallpaper and wall coverings installation. It is easy to apply, has high grab properties, quick setting and can be easily cleaned up with water.

Applications:

Suitable for wallpaper installation, general wallpaper and border repairs, include most types of wall-covering, including vinyl wallpaper, lining paper, etc.

NOTE: not for outdoor use

Directions:

- Surfaces must be clean, dry and free of dirt, grease, oil or water.
- VT-107, 125g bottle:**
Evenly apply the adhesive on the back of the wall-covering or wall and press together firmly and leave to dry.
VT-107, 1kg pail:
Apply adhesive on the back of the wallpaper with a brush or roller. Use a scraper to smoothen out wallpaper or any occurrence of air bubbles and wrinkles from the center towards outer edges within 5-10 minutes.
- Before the adhesive dries, clean up any excess adhesive with a damp cloth.

Caution

Contains a mixture of CMIT/MIT. May produce an allergic reaction. Keep out of reach of children. Safety data sheet available on request. For further health and safety information, consult the latest safety data sheet.

Storage:

Minimum of 12 months in tightly closed packing when stored in cool and dry place, below 30 °C.

Every endeavour has been made to ensure that the information given herein is true and reliable but it is given only for the guidance of our customers. The company cannot accept any responsibility for the loss or damage that may result from the use of the information, due to the possibility of variations of processing or working conditions and of workmanship outside our control. Users are advised to confirm suitability of this product by their own tests.

- END -