



Formulated For The Professionals

# VT-507 FloorSeal

## Two-component Epoxy Moisture Barrier

FloorSeal is a solvent-free, two-component epoxy moisture barrier that is specially formulated to form a protective coating against both moisture and vapor on flooring foundations. It has excellent adhesion and prepares the surface for subsequent flooring adhesives.

### Applications:

Suitable as a moisture barrier layer for various applications such as timber, vinyl flooring, concrete, fiber cement, stone, masonry, structural plywood, brick, etc. Promotes adhesion for porous substrates such as concrete.

### Applicable Test / Standard:

1. ASTM E96 / E96M - 16 - Standard Test Methods for Water Vapor Transmission of Materials

**Available colours:** White (Resin) and Dark grey (Hardener)

Item Code	Content	Carton Quantity
VT-507	4L Set (1:1) (2L Resin, 2L Hardener)	3 Set / Carton



### Features

- 1:1 mixing ratio
- Excellent water vapor retardant (ASTM E96/E96M-16)
- Solvent-free
- Low odor
- Non-flammable
- Bonds to most substrates



RESILIENT FLOORING



TIMBER FLOORING



**VITAL TECHNICAL SDN. BHD.** (No.: 589221-K)

No, 93, Jalan Industri 3/3, Rawang Integrated Industrial Park, 48000 Rawang, Selangor Darul Ehsan, Malaysia.

+603 6094 2088 (Tel) +603 6099 2930 (Fax)

sales@vitaltechnical.com

A MEMBER OF THE NIPPON PAINT GROUP

