#### VITAL TECHNICAL SDN. BHD.



#### **Technical Data Sheet**

# VT-560 No 1 Valve Grinding Paste



Issuance date: 28/09/10 Revision date: 12/10/20 Revision No.: 20-01

#### **Product Specification:**

Appearance: Grey Gel-like PasteChemical Type: Silicone Carbide

Odor : None Specific Gravity : 1.35 Shelf life : 24 months

Content : 42.5gm (1.5 oz) tube carded



## **Product Description:**

No. 1 Valve Grinding Paste is a fine grade paste used for the finishing work in the grinding application. It is specially formulated for valve grinding and seating applications in automotive, marine and industrial applications. It can be used for Hand or Machine Grinding.

## **Application:**

It is effective in removing burrs, surface defects, corrosions, gums and carbon deposits. It is also being used for lapping and grinding of chromium.

#### Features:

- Water Mixable
- · Hand or Machine Grinding
- Effective Removing Surface Defects & Carbon Deposits

### **Directions:**

- 1. Apply a liberal coating of paste to the valve surface.
- 2. Grind in usual manner.
- 3. Clean valve and seat with a damp cloth. Then wipe thoroughly with another dry cloth.
- 4. Mix with few drops of water for an easy to use paste.

#### Caution:

Contain Silicone Carbide and Ethylene Glycol. Avoid contact with eyes and prolonged contact with skin. For eyes contact, flush with water for 15 minutes. For skin contact, wash thoroughly with soap and water. Do not swallow. If swallowed, induce vomiting and seek medical attention.

Keep out of reach of children. Use in well ventilated areas.

#### Storage:

- Store in a dry and cool place with temperature below 30 °C.
- Use within 24 months from date of production.

Every endeavour has been made to ensure that the information given herein is true and reliable but it is given only for the guidance of our customers. The company will not accept any responsibility for the loss or damage that may result from the use of the information, due to the possibility of variation of processing or working conditions and of workmanship outside our control. Users are advised to confirm suitability of this product by their own tests.