

VITAL TECHNICAL SDN. BHD.

Technical Data Sheet

VT-183 / VT-183H Vital Shellac





Issuance date: 31/03/2008 Revision date: 10/12/2021 Revision No.: 21-04

VT-183 / VT-183H Vital Shellac

Colour

Dark Brown (VT-183) Honey (VT-183H)

PACKAGING

59 ml/ bottle (144 bottle / carton)

SHELF LIFE

24 months

STORAGE

Store in a dry and cool place with temperature around 30 °C

DESCRIPTION



Vital Shellac is a hard setting, fast drying liquid for gaskets repairing and sealing. It can seal the metal gasket and threaded connections for light duty service. It is suitable also for felt, paper, rubber and composite gaskets applications.

TECHNICAL DATA

Main Ingredient : Modified Rosin, alcohol

Flash Point : 12°C

Application Temperature : 4 °C to 38 °C Max. Operating Temperature : 180 °C

FEATURES

- Good Fuel Resistance
- Improved Reliability

APPLICATION

- Economical sealant for general assembly work
- Hose & threaded connections
- Close-fitting machined parts

APPLICATION DIRECTION

- Apply Vital Shellac with the brush provided on dry and clean surfaces. The surface should be free from oil, dirt, rust, and other contaminants.
- 2. The application temperature should be within the range of 4°C 38°C.
- 3. Generally, the wet film should be applied thin, approximately 0.25 mm, and uniform.
- 4. For bonding gaskets, apply on both surfaces. Allow to dry until surfaces are dry to the touch
- 5. Replace cap and tighten after use, store in cool, dry place.

CAUTION

Contains rosin; colophony. Highly flammable liquid and vapour. May cause an allergic skin reaction. Causes serious eye irritation. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. Safety data sheet available on request.

LEGAL NOTES

Every endeavour has been made to ensure that the information given herein is true and reliable but it is given only for the guidance of our customers. The company cannot accept any responsibility for the loss or damage that may result from the use of the information, due to the possibility of variations of processing or working conditions and of workmanship outside our control. Users are advised to confirm suitability of this product by their own tests.

www.vitaltechnical.com Page 1 of 1