


	VITAL TECHNICAL SDN. BHD.	  
	Technical Data Sheet	
	VT-2750 Water Tank Tape	

Issuance date: 05/10/19

Revision date: 08/10/20

Revision No.: 20-02

VT-2750 Water Tank Tape

PHYSICAL STATE

Principal composition:
Synthetic rubber

Appearance:
Black

Characteristics:
Tough and resilient

Sealing property:
Excellent

Water resistance:
Excellent

Toxicity:
Non-toxic

Service temperature:
-30 °C to 80 °C

Storage:
Avoid from direct sunlight exposure and heat source. Keep under cold and shaded place.

Shelf life:
18 months

Dimensions:
45mm x 4mm x 13m

DESCRIPTION



VT-2750 Water Tank Tape is an extruded, ever-tacky, waterproof, high performance butyl tape. It is non-toxic and safe for use in contact with drinking water.

TECHNICAL DATA	Penetration hardness	15 – 30
	Specific gravity	1.48 – 1.58

FEATURES	▪ Waterproof
	▪ Safe for drinking water

APPLICATION It is specifically formulated to permanently seal flange joints of water tanks.

APPLICATION DIRECTION

1. Ensure the target surfaces are clean, dry, dust-free and oil-free.
2. Peel off the release paper and press the sealant strip onto the surfaces to ensure good contact before fastening it with a bracket to achieve a permanent, water-tight seal.

CAUTION Keep out of reach of children. Safety data sheet available on request. For further health and safety information, consult the latest safety data sheet.

LEGAL NOTES Every endeavour has been made to ensure that the information given herein is true and reliable but it is given only for the guidance of our customers. The company cannot accept any responsibility for the loss or damage that may result from the use of the information, due to the possibility of variations of processing or working conditions and of workmanship outside our control. Users are advised to confirm suitability of this product by their own tests.