



VITAL TECHNICAL SDN. BHD.

Technical Data Sheet

VT-2760 Concrete Butyl (Manhole) Tape



Issuance date: 08/01/18

Revision date: 08/10/20

Revision No.: 20-01

VT-2760 Concrete Butyl (Manhole) Tape

Premium Preformed Butyl Sealant in Rope Form

PRINCIPAL COMPOSITION

Butyl Rubber

APPEARANCE

Grey
Black

ODOR

None or very little

PACKAGING

16 mm (D) x 3.8 m (L)
(10 rolls/carton)
**Other sizes available on request*

SHELF LIFE

18 months

STORAGE

Store in a dry and cool place with temperature below 30 °C

SERVICE TEMPERATURE

-15 °C to 80 °C

DESCRIPTION



VT-2760 Concrete Butyl (Manhole) Tape is supplied in rope form, primarily used as a gasketing material for fast and efficient sealing of joints in precast concrete. It contains a high proportion of butyl rubber and specially formulated with other solids, hence will not crack, shrink, or harden in its service. It provides excellent adhesion and cohesion to various substrates - concrete, metal, glass, wood, and painted surfaces.

TECHNICAL DATA

Solid content	: >99 %	
Hardness	: 50 ~ 65 x 0.1mm/5s, 50g	
Specific gravity	: 1.5 ± 0.1	
Tensile strength	: 160.96 kPa	ASTM C907-03
Peel strength	: 4.48 kPa	ASTM D903
Shear strength	: 116.21 kPa	ASTM C961-06
Elongation	: 106.12 %	ASTM C908
Water absorption	: 0.1 %	ASTM D570

FEATURES

- Provides permanently flexible watertight joints.
- Low moisture vapor transmission
- Coated release paper for easy installation.
- Long service life- will not shrink, harden or oxidize.
- Cohesive properties allow for joint movement.
- Resists water vapor permeation through the joint.
- Highly Compressible - accommodate minor imperfections in the mating surfaces.
- Tacky Characteristic - work on hard-to-bond surfaces.

APPLICATION

- Precast Concrete
- Vertical Panel Structures
- Sanitary Manhole Joints
- Box Culverts
- Concrete Pipes
- Underground Utility Vaults
- Stormwater Treatment Structures
- Irrigation and Drainage Systems
- Burial Vaults
- Elliptical/Arch Pipe
- Architectural Foundations
- On-Site Treatment Tanks
- Grease Interceptors
- Wet Wells
- Septic Tanks
- Utility Boxes

APPLICATION DIRECTION

- All installation surfaces must be clean and dry.
- Release sealant from release paper and press it sufficiently onto the surface for a complete contact.
- Store unused roll at cool and dry place and avoid unnecessary exposure to dust.

CAUTION

Keep out of reach of children. Safety data sheet available on request. For further health and safety information, consult the latest safety data sheet.

LEGAL NOTES

Every endeavour has been made to ensure that the information given herein is true and reliable, but it is given only for the guidance of our customers. The company cannot accept any responsibility for the loss or damage that may result from the use of the information, due to the possibility of variations of processing or working conditions and of workmanship outside our control. Users are advised to confirm suitability of this product by their own tests.