



609 High Performance Primer Part A

Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)
Issue date: 5/21/2025 Version: 1.0

SECTION 1: Identification

1.1. GHS Product identifier

Product form : Mixture
Product name : 609 High Performance Primer Part A
UN-No. (ADR) : 1263
Product group : Trade product

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Epoxy Primer

1.4. Supplier's details

Manufacturer

Vital Technical Sdn. Bhd.
No.93, Jalan Industri 3/3 Rawang Integrated Industrial Park,
48000 Rawang, Selangor, Malaysia.
T +603 60942088 - F +603 60992930

1.5. Emergency phone number

No additional information available

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification according to the United Nations GHS

Flammable liquids, Category 3	H226	On basis of test data
Skin corrosion/irritation, Category 2	H315	Calculation method
Serious eye damage/eye irritation, Category 1	H318	Calculation method
Skin sensitisation, Category 1	H317	Calculation method
Reproductive toxicity, Category 2	H361	Calculation method
Hazardous to the aquatic environment – Acute Hazard, Category 2	H401	Calculation method
Hazardous to the aquatic environment – Chronic Hazard, Category 2	H411	Calculation method

Full text of H-statements: see section 16

Adverse physicochemical, human health and environmental effects : Flammable liquid and vapour, Suspected of damaging fertility or the unborn child, Causes skin irritation, May cause an allergic skin reaction, Causes serious eye damage, Toxic to aquatic life, Toxic to aquatic life with long lasting effects.

2.2. GHS Label elements, including precautionary statements

Labelling according to the United Nations GHS

Hazard pictograms (GHS UN) :



Signal word (GHS UN) : Danger
Hazardous ingredients : 4-nonylphenol, branched; bis-[4-(2,3-epoxypropoxy)phenyl]propane
Hazard statements (GHS UN) : H226 - Flammable liquid and vapour
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage

609 High Performance Primer Part A

Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

Precautionary statements (GHS UN)

- H361 - Suspected of damaging fertility or the unborn child
- H411 - Toxic to aquatic life with long lasting effects
- : P203 - Obtain, read and follow all safety instructions before use.
- P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P233 - Keep container tightly closed.
- P240 - Ground and bond container and receiving equipment.
- P241 - Use explosion-proof equipment.
- P242 - Use non-sparking tools.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to the United Nations GHS
bis-[4-(2,3-epoxipropoxy)phenyl]propane	CAS-No.: 1675-54-3	10 – 30	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
4-nonylphenol, branched	CAS-No.: 84852-15-3	1 – 10	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Repr. 2, H361 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
xylene	CAS-No.: 1330-20-7	1 – 10	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315
4-hydroxy-4-methylpentan-2-one; diacetone alcohol	CAS-No.: 123-42-2	1 – 10	Eye Irrit. 2, H319

Full text of H-statements: see section 16

SECTION 4: First-aid measures

4.1. Description of necessary first-aid measures

- First-aid measures general : IF exposed or concerned: Get medical advice/attention.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
- First-aid measures after skin contact : Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
- First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms/effects, acute and delayed

- Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.
- Symptoms/effects after eye contact : Serious damage to eyes.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Treat symptomatically.

609 High Performance Primer Part A

Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Fire hazard : Flammable liquid and vapour.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective actions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and materials for containment and cleaning up

For containment : Collect spillage.
Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.
Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

609 High Performance Primer Part A

Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

xylene (1330-20-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Xylene, mixed isomers, pure
IOELV TWA (mg/m ³)	221 mg/m ³
IOELV STEL (mg/m ³)	442 mg/m ³
IOELV STEL (ppm)	100 ppm
Notes	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
USA - ACGIH - Occupational Exposure Limits	
Local name	Xylene, mixed isomers (Dimethylbenzene)
ACGIH TWA (ppm)	100 ppm
ACGIH STEL (ppm)	150 ppm
Remark (ACGIH)	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2021
USA - ACGIH - Biological Exposure Indices	
Local name	XYLENES (Technical or commercial grade)
Biological Exposure Indices (BEI)	1.5 g/g creatinine Parameter: Methylhippuric acids - Medium: urine - Sampling time: End of shift
Regulatory reference	ACGIH 2021

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment (PPE)

Hand protection : Protective gloves
Eye protection : Safety glasses
Skin and body protection : Wear suitable protective clothing
Respiratory protection : [In case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s)



8.4. Exposure limit values for the other components

No additional information available

SECTION 9: Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state : Liquid
Colour : Not available
Odour : Aromatic Hydrocarbon.
Odour threshold : Not available
Melting point : Not applicable
Freezing point : Not available

609 High Performance Primer Part A

Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

Boiling point	: 108 – 305 °C
Flammability	: Flammable liquid and vapour.
Lower explosion limit	: ≈ 1 vol %
Upper explosion limit	: ≈ 11 vol %
Flash point	: ≈ 51.51 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
pH solution	: Not available
Viscosity, kinematic (calculated value) (40 °C)	: 85.89 – 101.399 mm ² /s
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: 1.43 – 1.63 g/cm ³
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Solubility	: insoluble in water.
Viscosity, dynamic	: 140 – 145 KU
Particle size	: Not applicable

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
STOT-single exposure	: Not classified

609 High Performance Primer Part A

Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

STOT-repeated exposure : Not classified
Aspiration hazard : Not classified

609 High Performance Primer Part A	
Viscosity, kinematic	85.89 – 101.399 mm ² /s

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life. Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute) : Toxic to aquatic life.
Classification procedure (Hazardous to the aquatic environment, short-term (acute)) : Calculation method
Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.
Classification procedure (Hazardous to the aquatic environment, long-term (chronic)) : Calculation method

12.2. Persistence and degradability

609 High Performance Primer Part A	
Persistence and degradability	Not rapidly degradable
4-nonylphenol, branched (84852-15-3)	
Persistence and degradability	Not rapidly degradable
bis-[4-(2,3-epoxipropoxy)phenyl]propane (1675-54-3)	
Persistence and degradability	Not rapidly degradable
xylene (1330-20-7)	
Persistence and degradability	Not rapidly degradable
4-hydroxy-4-methylpentan-2-one; diacetone alcohol (123-42-2)	
Persistence and degradability	Not rapidly degradable

12.3. Bioaccumulative potential

609 High Performance Primer Part A	
Bioaccumulative potential	No additional information available

12.4. Mobility in soil

609 High Performance Primer Part A	
Mobility in soil	No additional information available

12.5. Other adverse effects

Ozone : Not classified
Other adverse effects : No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information : Flammable vapours may accumulate in the container.

609 High Performance Primer Part A

Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

SECTION 14: Transport information

In accordance with UN RTDG / IMDG / IATA

UN RTDG	IMDG	IATA
14.1. UN number		
1263	1263	1263
14.2. UN Proper Shipping Name		
PAINT	PAINT	Paint
Transport document description		
UN 1263 PAINT, 3, III, ENVIRONMENTALLY HAZARDOUS	UN 1263 PAINT, 3, III, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1263 Paint, 3, III, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)		
3	3	3
		
14.4. Packing group		
III	III	III
14.5. Environmental hazards		
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes
No supplementary information available		

14.6. Special precautions for user

UN RTDG

Special provisions (UN RTDG) : 163, 223, 367
Limited quantities (UN RTDG) : 5L
Excepted quantities (UN RTDG) : E1
Packing instruction (UN RTDG) : P001, IBC03, LP01
Special packing provisions (UN RTDG) : PP1
Portable tank and bulk container special instructions (UN RTDG) : T2
Portable tank and bulk container special provisions (UN RTDG) : TP1, TP29

IMDG

Special provisions (IMDG) : 163, 223, 367, 955
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E1
Packing instructions (IMDG) : P001, LP01
Special packing provisions (IMDG) : PP1
IBC packing instructions (IMDG) : IBC03
Tank instructions (IMDG) : T2
Tank special provisions (IMDG) : TP1, TP29
EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage) : S-E - SPILLAGE SCHEDULE Echo - FLAMMABLE LIQUIDS, FLOATING ON WATER
Stowage category (IMDG) : A
Properties and observations (IMDG) : Miscibility with water depends upon the composition.

IATA

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y344

609 High Performance Primer Part A

Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provisions (IATA)	: A3, A72, A192
ERG code (IATA)	: 3L

14.7. Transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question

No additional information available

SECTION 16: Other information

Issue date : 5/21/2025

Abbreviations and acronyms :

- CAS-No. - Chemical Abstract Service number
- ATE - Acute Toxicity Estimate
- EC50 - Median effective concentration
- EC-No. - European Community number
- IATA - International Air Transport Association
- IMDG - International Maritime Dangerous Goods
- LC50 - Median lethal concentration
- LD50 - Median lethal dose
- LOAEL - Lowest Observed Adverse Effect Level
- N.O.S. - Not Otherwise Specified
- NOAEC - No-Observed Adverse Effect Concentration
- NOAEL - No-Observed Adverse Effect Level
- NOEC - No-Observed Effect Concentration
- OEL - Occupational Exposure Limit
- SDS - Safety Data Sheet

Full text of H-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Acute 2	Hazardous to the aquatic environment – Acute Hazard, Category 2
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Repr. 2	Reproductive toxicity, Category 2
Skin Corr. 1B	Skin corrosion/irritation, Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1

609 High Performance Primer Part A

Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

Full text of H-statements:	
H226	Flammable liquid and vapour
H302	Harmful if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H361	Suspected of damaging fertility or the unborn child
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects

Safety Data Sheet (SDS), UN

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.