

100% Neutral Silicone

A one-component, neutral-cure, high-performance, non-staining silicone sealant specially formulated to prevent staining on porous substrates where aesthetic considerations are important. It offers ±25% movement capability hence provides excellent performance in dynamic movement joints. It offers superior adhesion to a wide variety of building materials. It has excellent resistance to weathering, UV radiation, vibration, moisture, ozone, temperature extremes, airborne pollutants, etc.

Applications:

Designed for weatherproofing sensitive natural stone. Also suited for weatherproof seal on most common building materials such as aluminium, galvanised and zinc-coated steel, painted surfaces, glass, brick, and concrete.

Applicable Test / Standard:

- 1. ASTM C920, Type S, Grade NS, Class 25, Use A, G & O
- 2.ASTM C1248: 2018 Standard Test Method For Staining Of Porous Substrate By Joint Sealants
- 3. Low VOC USEPA Method 24 under SCAQMD Rule 1168 & USEPA Method 310







Standard Colours: White, Black and Grey

Item Code	Content	Carton Quantity
VT-291	300 ml Cartridge	24 / Carton
VT-291S	600 ml Sausage	20 / Carton

Features

- Non-staining on natural stone
- ±25% movement capability
- Excellent UV and weathering resistance



NATURAL STONE



STONE FACADE



WEATHERSEAL



VITAL TECHNICAL SDN. BHD. Co.No.: 200201021558 (589221-K)

- (Fax) +603 6094 2088 (Tel) +603 6099 2930 (Fax)
- sales@vitaltechnical.com
- www.vitaltechnical.com







