



VITAL TECHNICAL SDN. BHD.

Technical Data Sheet

VT-2730
Roofing Tape



Issuance date: 27/04/17

Revision date: 24/11/20

Revision No.: 20-02

VT-2730 Roofing Tape

Principal Composition:

Butyl rubber

Appearance:

Grey

Odour:

None or very little

PACKAGING

9.0mm x 2.5mm x 19m
(20 rolls/carton)

12mm x 2.5mm x 19m
(20 rolls/carton)

19mm x 2.5mm x 19m
(20 rolls/carton)

SERVICE TEMPERATURE

-15 °C to 80 °C

SHELF LIFE

18 months

STORAGE

Store away from direct sunlight and heat source, keep under cold and shaded place.

DESCRIPTION



VT-2730 Roofing Tape is a double-sided butyl adhesive tape that has high cohesive and adhesive strengths. It contains anti-oxidants, fungicides and anti-bacterial agents and available in several sizes.

TECHNICAL DATA	Needle penetration	: 50 – 65
	Specific gravity	: 1.46 – 1.56

FEATURES	<ul style="list-style-type: none"> High cohesive and adhesive strengths Anti-oxidants, fungicides, and anti-bacterial agents
-----------------	--

APPLICATION	It is used on built-up roof to seal end laps and the side laps of the top (weather) sheet. Other applications are sealing the underneath of the solar panels during installation, around rooflights, gutters and flashings. It is suitable for both clay and concrete tiles as well as metal roofing installation onto concrete, metal or wooden structures. The tape can also be used on glass, polycarbonate, uPVC, epoxy coated surfaces and fibre cement boards.
--------------------	--

APPLICATION DIRECTION	<ol style="list-style-type: none"> Ensure that surfaces are clean, dry, dust free, oil free and sound. Release sealant from release paper and press it sufficiently onto the surface for a complete contact.
------------------------------	--

CAUTION	Keep out of reach of children. Safety data sheet available on request. For further health and safety information, consult the latest safety data sheet.
----------------	---

LEGAL NOTES	Every endeavour has been made to ensure that the information given herein is true and reliable but it is given only for the guidance of our customers. The company cannot accept any responsibility for the loss or damage that may result from the use of the information, due to the possibility of variations of processing or working conditions and of workmanship outside our control. Users are advised to confirm suitability of this product by their own tests.
--------------------	---