



VITAL TECHNICAL SDN. BHD.

Technical Data Sheet

VT-2740
Vacuum Bagging Tape



Issuance date: 27/04/17

Revision date: 04/02/21

Revision No.: 21-01

VT-2740 Vacuum Bagging Tape

Principal Composition:
Synthetic rubber

Appearance:
Yellow
Off white

Odour:
None or very little

PACKAGING

3mm x 13mm x 19m
(20 rolls/carton)

3mm x 13mm x 15m
(20 rolls/carton)

1.5mm x 13mm x 23m
(20 rolls/carton)


SERVICE TEMPERATURE
-20 °C to 200 °C

SHELF LIFE
18 months

STORAGE
Store away from direct sunlight and heat source, keep under cold and shaded place.

DESCRIPTION

VT-2740 Vacuum Bagging Tape is an ever-tacky butyl sealant tape with good adhesion that can seal against water and air.



TECHNICAL DATA		
Total Solids	:	> 99 %
Needle penetration	:	65 – 75 x 0.1mm / 5s, 50g
Specific gravity	:	1.15 – 1.25
Peel adhesion 90° (aluminium)	:	~10 N
Maximum tensile strength	:	~54 kPa
Elongation at break	:	> 50 %

- FEATURES**
- Good adhesion
 - Seal against water and air

APPLICATION It is ideal for use on composite tool surfaces and easy to remove from the mould. Forms tight seals on plastics, metal, glass, wood and concrete.

- APPLICATION DIRECTION**
1. Ensure that surfaces are clean, dry, dust free, oil free and sound.
 2. Release sealant from release paper and apply pressure sufficiently onto the surface for a complete contact.

CAUTION Keep out of reach of children. Safety data sheet available on request. For further health and safety information, consult the latest safety data sheet.

LEGAL NOTES Every endeavour has been made to ensure that the information given herein is true and reliable but it is given only for the guidance of our customers. The company cannot accept any responsibility for the loss or damage that may result from the use of the information, due to the possibility of variations of processing or working conditions and of workmanship outside our control. Users are advised to confirm suitability of this product by their own tests.