



Technical Data Sheet

VT-428 VitalFlash

Bitumen Flashing Tape



Issuance date: 08/04/2021

Revision date: 08/12/2021

designed to match the common roof colours.

Revision No.: 21-01

VT-428 VitalFlash Bitumen Flashing Tape

DESCRIPTION

APPEARANCE Black tape

AVAILABLE COLOURS Maroon Black Red

ODOUR None or very little

WATER RESISTANCE Excellent

PACKAGING 100mm x 10m 300mm x 10m

SHELF LIFE 18 months

STORAGE

Store in a dry and cool place with temperature below 30 °C

APPLICATION TEMPERATURE

5 °C – 40 °C

TECHNICAL DATA	Specific gravity Softening point Peel strength	: 1.10 – 1.13 : 80 °C : 20 N
FEATURES	 Adheres well to most construction materials. Simple installation. Neat finish Easy to use Economical 	
APPLICATION	It is specially formulated for applications such as: Abutment Ridge and hip 	
APPLICATION DIRECTION	 FOR ABUTMENT INSTALLATION: Surfaces must be clean, dry and free of dirt, grease, oil or water. Roll out the necessary length of VitalFlash and align it to the application area. Remove the release paper and apply VitalFlash onto the surfaces. Ensure both surfaces have good contact. A roller might be necessary to ensure goo contact between both surfaces. FOR HIP AND RIDGE INSTALLATION: Surfaces must be clean, dry and free of dirt, grease, oil or water. The tiles along the hip tree should have sufficient gap for the application. Roll out the necessary length of VitalFlash and align it to the application area. Remove the release paper and apply VitalFlash onto the surfaces. Ensure both surfaces have good contact. A roller might be necessary to ensure good contact between both surfaces. 	
CAUTION	Keep out of reach of children. Safety data sheet available on request. For further heal and safety information, consult the latest safety data sheet.	
LEGAL NOTES	Every endeavour has been made to ensure that the information given herein is true an reliable, but it is given only for the guidance of our customers. The company cannot accept any responsibility for the loss or damage that may result from the use of the information due to the possibility of variations of processing or working conditions and of workmanshi outside our control. Users are advised to confirm suitability of this product by their ow tests.	

VT-428 VitalFlash is a versatile and waterproof dry fix solution that is specially formulated

to adhere to the various conditions necessary for roofing applications such as abutment as well as ridge and hip. VitalFlash is also UV resistant due to the coloured outer layer,