

Issuance date: 06/06/11

Revision date: 06/05/2025

Revision No.: R25-01

Product Specification:

Colour : Clear
Working time : 5 – 20 minutes
Specific gravity : 0.80 ± 0.03
Solid content : 37 ± 1 %
Viscosity : Medium
Shelf life : 24 months
Features : Clear colour
: Bond most materials
: Polystyrene-safe

Packaging

Product Code	Content	Inner Box	Carton
T-910V	7 ml x 12 tubes carded	-	48
VT-911	7 ml x 2 tubes carded	12	288
VT-912	20 ml tube boxed	20	200
VT-912C	20 ml tube carded	12	144
VT-913	7 ml tube carded	12	288
VT-914	125 ml tube boxed	12	144
VT-914C	125 ml tube carded	12	72



Visit product page:

<https://www.vitaltechnical.com/product/super-glue-and-all-purpose-adhesive/?vt=vt-910-vt-911-vt-912-vt-913-vt-914>



Product Description:

A clear all purpose adhesive suitable for most types of household repair and craft works. It is fast curing and will not attack polystyrene (Styrofoam).

Applications:

Bonds wood, cardboard, paper, fabric, leather, pottery, glass, china, marble, metal, felt, straw, hard foam, polystyrene (Styrofoam) and many types of plastic.

Directions:

1. Surfaces must be clean, dry and free of dirt, grease, oil or water.
2. Spread evenly on both side of surfaces, leave to dry for 5 minutes – 20 minutes, then press together firmly.
3. Adjustments will no longer be possible. Close the cap after use and store in a cool, dry place.

Caution

Highly flammable liquid and vapour. Causes skin irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing fumes. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. If skin irritation occurs: Get medical advice/attention. Collect spillage. Store in a well-ventilated place. Keep cool. Safety data sheet available on request. For further health and safety information, consult the latest safety data sheet.

Storage:

- Stored in cool and dry place, below 30 °C to gives optimum storage stability.

Every endeavour has been made to ensure that the information given herein is true and reliable but it is given only for the guidance of our customers. The company cannot accept any responsibility for the loss or damage that may result from the use of the information, due to the possibility of variations of processing or working conditions and of workmanship outside our control. Users are advised to confirm suitability of this product by their own tests.