



Formulated For The Professionals
Adhesives & Sealants

VT-638FC MS Seam Sealant

Advanced MS Polymer

MS Seam Sealant is a one-component, high-performance sealant formulated based on advanced MS Polymer technology. This sealant is free of solvent and, isocyanate, making it a more environmentally- and human-friendly product. It is also free of silicone oil, thus will not cause fluid streaking issues on vertical surfaces. It features fast-drying speed, and excellent UV, weather, and temperature resistance. The adhesion on various substrates is excellent even without the use of primer, and the sealant is paintable with most types of common industrial paints.

Applications:

Ideal for making permanent elastic seals of high bonding strength, especially interior and exterior body seams and joints of automobile / truck / coach / train / ship & boat. Its great adhesion on various substrates like metal and FRP, without the need of applying primer when using traditional sealant, has made it a great choice in modern manufacturing and repair works.

In shipping container manufacturing, it can be used for watertight sealing applications like sealing gaps between side and roof panels, CSC plates, bottom rails before laying wooden floorboards, door vents, rivets, etc. Compared with solvent based synthetic rubber sealants, VT-638FC has better weathering resistance when used in exterior applications, and when used to seal interior gaps, it will cause less odor as it does not contain solvent. It is also suitable for various other high-performance, elastic sealing or bonding in construction and industrial applications, especially when painting over sealant is required.

Available colours: White, Beige and Black

Item Code	Content	Carton Quantity
VT-638FC	290 ml Cartridge	20 / Carton
VT-638FCS	600 ml Sausage	20 / Carton



Features

- High performance and elastic
- Fast drying
- Paintable
- Low odour
- Environmentally- & human-friendly
- Primerless bonding to most substrates
- Isocyanate-free – No air bubbling
- Solvent-free – No shrinkage
- Silicone-free – No fluid streaking



VEHICLE
SEAM SEALING



GAPS SEALING



CSC PLATE



BOLT / RIVET



VITAL TECHNICAL SDN. BHD. (No.: 589221-K)

+603 6094 2088 (Tel) +603 6099 2930 (Fax)

sales@vitaltechnical.com

www.vitaltechnical.com



A member of

NIPPON PAINT