



VT-665 Primerless Auto Glass Sealant

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830
Issue date: 22/10/2020 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : VT-665 Primerless Auto Glass Sealant
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use, Consumer use
Use of the substance/mixture : Sealants

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Manufacturer

Vital Technical Sdn. Bhd.
No.93, Jalan Industri 3/3
Rawang Integrated Industrial Park,
48000 Rawang, Selangor, Malaysia.
T +603 60942088 - F +603 60992930
sales@vitaltechnical.com

1.4. Emergency telephone number

No additional information available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Serious eye damage/eye irritation, Category 2	H319
Skin sensitisation, Category 1	H317
Reproductive toxicity, Category 1A	H360
Hazardous to the aquatic environment — Chronic Hazard, Category 3	H412
Full text of H statements : see section 16	

Adverse physicochemical, human health and environmental effects

May damage fertility or the unborn child. May cause an allergic skin reaction. Causes serious eye irritation. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07

GHS08

Signal word (CLP) :

Danger

Contains

N-(3-(TRIMETHOXYSILYL)PROPYL)ETHYLENEDIAMINE; DIBUTYLBIS(PENTANE-2,4-DIONATO-O,O')TIN

VT-665 Primerless Auto Glass Sealant

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hazard statements (CLP)	: H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation. H360 - May damage fertility or the unborn child. H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P201 - Obtain special instructions before use. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P308+P313 - IF exposed or concerned: Get medical advice/attention. P321 - Specific treatment (see supplemental first aid instruction on this label). P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
Labelling according to: exemption for packages of a capacity of 125ml or less	
Hazard pictograms (CLP)	:   GHS07 GHS08
Signal word (CLP)	: Danger
Hazardous ingredients	: N-(3-(TRIMETHOXYSILYL)PROPYL)ETHYLENEDIAMINE; DIBUTYLBIS(PENTANE-2,4-DIONATO-O,O')TIN
Hazard statements (CLP)	: H317 - May cause an allergic skin reaction. H360 - May damage fertility or the unborn child. H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P201 - Obtain special instructions before use. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P308+P313 - IF exposed or concerned: Get medical advice/attention. P321 - Specific treatment (see supplemental first aid instruction on this label). P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
N-(3-(TRIMETHOXYSILYL)PROPYL)ETHYLENEDIAMINE	(CAS-No.) 1760-24-3 (EC-No.) 217-164-6	1 – 10	Eye Dam. 1, H318 Skin Sens. 1, H317 STOT SE 3, H335
TRIMETHOXYVINYL SILANE	(CAS-No.) 2768-02-7 (EC-No.) 220-449-8	1 – 10	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332
BIS(2,2,6,6-TETRAMETHYL-4-PIPERIDYL)SEBACATE	(CAS-No.) 52829-07-9 (EC-No.) 258-207-9	0.1 – 1	Eye Dam. 1, H318 Aquatic Chronic 1, H410

VT-665 Primerless Auto Glass Sealant

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

DIBUTYLBIS(PENTANE-2,4-DIONATO-O,O')TIN substance listed as REACH Candidate	(CAS-No.) 22673-19-4 (EC-No.) 245-152-0	0.1 – 1	Acute Tox. 4 (Oral), H302 Skin Corr. 1A, H314 Skin Sens. 1, H317 Muta. 2, H341 Repr. 1A, H360 STOT SE 1, H370 STOT RE 1, H372 Aquatic Chronic 1, H410
--	--	---------	--

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam.
------------------------------	----------------------------------

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Toxic fumes may be released.
--	--------------------------------

5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Only qualified personnel equipped with suitable protective equipment may intervene. Avoid breathing dust/fume/gas/mist/vapours/spray.
----------------------	---

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

VT-665 Primerless Auto Glass Sealant

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Mechanically recover the product. Notify authorities if product enters sewers or public waters.
- Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.
- Hygiene measures : Separate working clothes from town clothes. Launder separately. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

1,2-BENZENEDICARBOXYLIC ACID,DI-C8-10-BRANCHED ALKYL ESTERS,C9-RICH (68515-48-0)	
Denmark - Occupational Exposure Limits	
Grænseværdi (8 timer) (mg/m ³)	≈ 3 mg/m ³
Ireland - Occupational Exposure Limits	
OEL (8 hours ref) (mg/m ³)	≈ 5 mg/m ³
United Kingdom - Occupational Exposure Limits	
WEL TWA (mg/m ³)	≈ 5 mg/m ³

CARBON BLACK (1333-86-4)

Belgium - Occupational Exposure Limits	
Limit value [mg/m ³]	≈ 3 mg/m ³
Denmark - Occupational Exposure Limits	
Grænseværdi (8 timer) (mg/m ³)	≈ 3.5 mg/m ³
Finland - Occupational Exposure Limits	
HTP-arvo (8h) (mg/m ³)	≈ 3.5 mg/m ³
France - Occupational Exposure Limits	
VME [mg/m ³]	≈ 3.5 mg/m ³

VT-665 Primerless Auto Glass Sealant

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

CARBON BLACK (1333-86-4)	
Ireland - Occupational Exposure Limits	
OEL (8 hours ref) (mg/m ³)	≈ 3 mg/m ³
Poland - Occupational Exposure Limits	
NDS (mg/m ³)	≈ 4 mg/m ³
Spain - Occupational Exposure Limits	
VLA-ED (mg/m ³)	≈ 3.5 mg/m ³
Sweden - Occupational Exposure Limits	
nivågränsvärde (NVG) (mg/m ³)	≈ 3 mg/m ³
United Kingdom - Occupational Exposure Limits	
WEL TWA (mg/m ³)	≈ 3.5 mg/cm ³
USA - ACGIH - Occupational Exposure Limits	
Local name	Carbon black
ACGIH TWA (mg/m ³)	3 mg/m ³ (I - Inhalable particulate matter)
Remark (ACGIH)	TLV® Basis: Bronchitis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2020

CALCIUM CARBONATE (471-34-1)	
France - Occupational Exposure Limits	
VME [mg/m ³]	≈ 10 mg/m ³
Ireland - Occupational Exposure Limits	
OEL (8 hours ref) (mg/m ³)	≈ 10 mg/m ³
Latvia - Occupational Exposure Limits	
OEL TWA (mg/m ³)	≈ 6 mg/m ³
Poland - Occupational Exposure Limits	
NDS (mg/m ³)	≈ 10 mg/m ³
United Kingdom - Occupational Exposure Limits	
WEL TWA (mg/m ³)	≈ 10 mg/m ³
Switzerland - Occupational Exposure Limits	
MAK (mg/m ³)	≈ 3 mg/m ³

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

VT-665 Primerless Auto Glass Sealant

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

8.2.2.3. Respiratory protection

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Paste.
Colour	: Black.
Odour	: odourless.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: Not applicable
Boiling point	: No data available
Flash point	: Not applicable
Auto-ignition temperature	: Not applicable
Decomposition temperature	: No data available
Flammability (solid, gas)	: Non flammable.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: ≈ 1.33
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: Not applicable
Viscosity, dynamic	: No data available
Explosive properties	: No data available

VT-665 Primerless Auto Glass Sealant

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Oxidising properties : No data available
Explosive limits : Not applicable

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

N-(3-(TRIMETHOXYSILYL)PROPYL)ETHYLENEDIAMINE (1760-24-3)

LD50 oral rat	2295 mg/kg
LD50 dermal	2000 mg/kg

TRIMETHOXYVINYLSILANE (2768-02-7)

LD50 oral rat	7120 mg/kg
LD50 dermal	3259 mg/kg

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitisation : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Reproductive toxicity : May damage fertility or the unborn child.

STOT-single exposure : Not classified

VT-665 Primerless Auto Glass Sealant

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

N-(3-(TRIMETHOXYSILYL)PROPYL)ETHYLENEDIAMINE (1760-24-3)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

DIBUTYLBIS(PENTANE-2,4-DIONATO-O,O')TIN (22673-19-4)

STOT-single exposure	Causes damage to organs.
----------------------	--------------------------

STOT-repeated exposure : Not classified

DIBUTYLBIS(PENTANE-2,4-DIONATO-O,O')TIN (22673-19-4)

STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
------------------------	---

Aspiration hazard : Not classified

VT-665 Primerless Auto Glass Sealant

Viscosity, kinematic	Not applicable
----------------------	----------------

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.
Not rapidly degradable

TRIMETHOXYVINYL SILANE (2768-02-7)

LC50 fish 1	191 mg/l
EC50 other aquatic organisms 1	168.7 mg/l

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Component

DIBUTYLBIS(PENTANE-2,4-DIONATO-O,O')TIN (22673-19-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
--	---

12.6. Other adverse effects

No additional information available

VT-665 Primerless Auto Glass Sealant

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
UN -	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Dangerous for the environment : No	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

14.6. Special precautions for user

Overland transport

No data available

Transport by sea

Not applicable

Air transport

Not applicable

Inland waterway transport

Not applicable

Rail transport

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains a substance on the REACH candidate list in concentration $\geq 0.1\%$ or with a lower specific limit: Dibutylbis(pentane-2,4-dionato-O,O')tin (EC 245-152-0, CAS 22673-19-4)

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VT-665 Primerless Auto Glass Sealant

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

15.1.2. National regulations

Germany

Employment restrictions : Observe restrictions according Act on the Protection of Working Mothers (MuSchG)
Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG)

Water hazard class (WGK) : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1)

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

ABM category : Z(1) - non biodegradable substances with hazardous properties for humans and the environment (carcinogenicity/ mutagenicity/ reprotoxicity/bioaccumulative potential/ toxicity or persistence)

SZW-lijst van kankerverwekkende stoffen : None of the components are listed

SZW-lijst van mutagene stoffen : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : DIBUTYLBIS(PENTANE-2,4-DIONATO-O,O')TIN is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : DIBUTYLBIS(PENTANE-2,4-DIONATO-O,O')TIN is listed

Denmark

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BLV	Biological limit value
CAS-No.	Chemical Abstract Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
EC-No.	European Community number
EN	European Standard
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration

VT-665 Primerless Auto Glass Sealant

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative
WGK	Water Hazard Class

Full text of H- and EUH-statements:	
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Flam. Liq. 3	Flammable liquids, Category 3
Muta. 2	Germ cell mutagenicity, Category 2
Repr. 1A	Reproductive toxicity, Category 1A
Skin Corr. 1A	Skin corrosion/irritation, Category 1, Sub-Category 1A
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1
STOT SE 1	Specific target organ toxicity — single exposure, Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H360	May damage fertility or the unborn child.
H370	Causes damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.