




| | | |
|---|--|---|
|  | VITAL TECHNICAL SDN. BHD. |   |
| | Technical Data Sheet | |
| | VT-766 Premium D2 Wood Glue | |

Issuance date: 03/10/2024

Revision date:

Revision No.: -

Product Specification:

| | |
|------------------------------------|---|
| Appearance | : Viscous liquid |
| Solid content | : 38.0 - 40.0% |
| pH | : 4.0 - 5.0 |
| Viscosity (Brookfield LV 3 @ 5rpm) | : 8,000 - 12,000 cPs |
| Specific Gravity | : 1.05 - 1.10 |
| Colour | : Light yellow (Wet) : Yellowish transparent (Dry) |
| Wet tack | : Aggressive |
| Flammability | : Non-flammable |
| Shelf life | : 24 months |
| Features | : Water-resistant D2 : Indoor use : Easy to spread : High bond strength : Fast curing : Forms thin gapless layer when set : Non-toxic, solvent free and low odour |

Packaging

| Product Code | Content | Inner Box | Carton |
|--------------|--------------|-----------|--------|
| VT-766-125 | 125 g bottle | 12 | 144 |
| VT-766-250 | 250 g bottle | 12 | 72 |
| VT-766-500 | 500 g bottle | - | 24 |

Product Description:

A premium D2-grade wood glue formulated for indoor woodworking applications with limited exposure to high humidity. It offers quick setting, superior bonding strength, and versatility across various porous substrates. It is non-toxic, solvent free and easy cleans up with water.

Applications:

Suitable for indoor wood joining, furniture repair, wooden frames, and woodworking projects which have limited exposure to high humidity. Not for continuous submersion or use below the waterline.

Directions:

1. Surfaces must be clean, dry and free of dirt, grease, oil or water.
2. Apply the adhesive on both surfaces if the material is porous. Press together firmly and leave to dry.
3. Replace cap after use and store in a cool, dry place.

Caution:

Safety data sheet available on request. For further health and safety information, consult the latest safety data sheet.

Storage:

Minimum of 24 months in tightly closed packing when stored in cool and dry place, below 30 °C.

Every endeavour has been made to ensure that the information given herein is true and reliable but it is given only for the guidance of our customers. The company cannot accept any responsibility for the loss or damage that may result from the use of the information, due to the possibility of variations of processing or working conditions and of workmanship outside our control. Users are advised to confirm suitability of this product by their own tests.

- END -