

A premium D2-grade wood glue formulated for indoor woodworking applications with limited exposure to high humidity. It offers quick setting, superior bonding strength, and versatility across various porous substrates. It is non-toxic, solvent free and easy to clean up with water.

## Applications:

Suitable for indoor wood joining, furniture repair, wooden frames, and woodworking projects which have limited exposure to high humidity. Not for continuous submersion or use below the waterline.







Available colour: Light yellow (Wet)
Yellowish transparent (Dry)

1	Item Code	Content	Inner Box	Carton Quantity
	VT-766125	125 g Bottle	12	144 / Carton
	VT-766250	250 g Bottle	12	72 / Carton
	VT-766500	500 g Bottle	-	24 / Carton
	VT-7661K	1.0 kg Bottle	-	12 / Carton
	VT-7664K	4.0 kg Pail	-	6 / Carton

## Features

- Water-resistant D2
- Indoor use
- Easy to spread
- High bond strength
- Fast curing
- Forms thin gapless layer when set
- Non-toxic, solvent free and low odour



PARQUET



WOOD BONDING



FURNITURE REPAIR



## VITAL TECHNICAL SDN. BHD. Co.No.: 200201021558 (589221-K)

- (Fax) +603 6094 2088 (Tel) +603 6099 2930 (Fax)
- sales@vitaltechnical.com
- www.vitaltechnical.com







