

Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)
Issue date: 1/24/2024 Revision date: 8/26/2025 Supersedes: 1/24/2024 Version: 1.1

SECTION 1: Identification

1.1. GHS Product identifier

Product form : Mixture

Product name : VT-239 Clear Nails

UN-No. (ADR) : 1133

Product group : Trade product

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Adhesives

1.4. Supplier's details

Manufacturer

Vital Technical Sdn. Bhd.

No.93, Jalan Industri 3/3 Rawang Integrated Industrial Park,

48000 Rawang, Selangor, Malaysia.

T +603 60942088 - F +603 60992930

1.5. Emergency phone number

No additional information available

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification according to the United Nations GHS

Flammable liquids, Category 2	H225	On basis of test data
Skin corrosion/irritation, Category 2	H315	Calculation method
Serious eye damage/eye irritation, Category 2	H319	Calculation method
Reproductive toxicity, Category 2	H361	Calculation method
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336	Calculation method
Specific target organ toxicity – Repeated exposure, Category 2	H373	Calculation method
Aspiration hazard Not classified		Calculation method
Hazardous to the aquatic environment – Chronic Hazard, Category 3	H412	Calculation method

Full text of H-statements: see section 16

Adverse physicochemical, human health and

environmental effects

: Highly flammable liquid and vapour, Suspected of damaging fertility or the unborn child, May cause damage to organs through prolonged or repeated exposure, May cause drowsiness or dizziness, Causes skin irritation, Causes serious eye irritation, Harmful to aquatic life with long lasting effects.

2.2. GHS Label elements, including precautionary statements

Labelling according to the United Nations GHS

Hazard pictograms (GHS UN)







Signal word (GHS UN)

ignal word (Gris Giv) . Dangi

Hazardous ingredients : butanone; ethyl methyl ketone; NAPHTHA (PETROLEUM), HYDROTREATED LIGHT

Hazard statements (GHS UN) : H225 - Highly flammable liquid and vapour

H315 - Causes skin irritation

Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

H361 - Suspected of damaging fertility or the unborn child

H373 - May cause damage to organs through prolonged or repeated exposure

H412 - Harmful to aquatic life with long lasting effects

Precautionary statements (GHS UN) : P203 - Obtain, read and follow all safety instructions before use.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P233 - Keep container tightly closed.

P240 - Ground and bond container and receiving equipment.

P241 - Use explosion-proof equipment.

P242 - Use non-sparking tools.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to the United Nations GHS
butanone; ethyl methyl ketone	CAS-No.: 78-93-3	10 – 30	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT	CAS-No.: 64742-49-0	10 – 30	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY	CAS-No.: 64742-48-9	1 – 10	Flam. Liq. 4, H227 Asp. Tox. 1, H304

Full text of H-statements: see section 16

SECTION 4: First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin

irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Irritation.
Symptoms/effects after eye contact : Eye irritation.

Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media : Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Water spray.

5.2. Specific hazards arising from the chemical

Fire hazard : Highly flammable liquid and vapour. Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective actions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe

dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and materials for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or

public waters.

Other information : Dispose of materials or solid residues at an authorized site.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Use

only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this

product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

8/26/2025 (Revision date) EN (English) 3/9

Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

butanone; ethyl methyl ketone (78-93-3)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	Butanone	
IOELV TWA (mg/m³)	600 mg/m³	
IOELV STEL (mg/m³)	900 mg/m³	
IOELV STEL (ppm)	300 ppm	
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC	
USA - ACGIH - Occupational Exposure Limits		
Local name	Methyl ethyl ketone (MEK)	
ACGIH TWA (ppm)	200 ppm	
ACGIH STEL (ppm)	300 ppm	
Remark (ACGIH)	TLV® Basis: URT irr; CNS & PNS impair. Notations: BEI	
Regulatory reference	ACGIH 2021	
USA - ACGIH - Biological Exposure Indices		
Local name	METHYL ETHYL KETONE	
Biological Exposure Indices (BEI)	2 mg/l Parameter: Methyl ethyl ketone - Medium: urine - Sampling time: End of shift - Notations: Ns	
Regulatory reference	ACGIH 2021	
NAPHTHA (PETROLEUM), HYDROTREATED I	LIGHT (64742-49-0)	
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	Cyclohexane	
IOELV TWA (mg/m³)	700 mg/m³	
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC	
USA - ACGIH - Occupational Exposure Limits		
Local name	Cyclohexane	
ACGIH TWA (ppm)	100 ppm	
Remark (ACGIH)	TLV® Basis: CNS impair	
Regulatory reference	ACGIH 2021	
USA - ACGIH - Biological Exposure Indices		
Local name	n-HEXANE	
Biological Exposure Indices (BEI)	0.5 mg/l Parameter: 2,5-Hexanedione (without hydrolysis) - Medium: urine - Sampling time: End of shift	
Regulatory reference	ACGIH 2021	

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment (PPE)

Materials for protective clothing :

8/26/2025 (Revision date) EN (English) 4/9

Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

Hand protection : Protective gloves
Eye protection : Safety glasses

Skin and body protection : Wear suitable protective clothing

Respiratory protection : [In case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s)







8.4. Exposure limit values for the other components

No additional information available

SECTION 9: Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state : Liquid Appearance Paste Colour Translucent. Odour Characteristic. Odour threshold Not available : Not applicable Melting point Freezing point : Not available : > 68 °C Boiling point

Flammability : Highly flammable liquid and vapour.

Lower explosion limit : Not available Upper explosion limit : Not available Flash point : < 23 °C Auto-ignition temperature : Not available Decomposition temperature : Not available : Not available pH solution : Not available Viscosity, kinematic (calculated value) (40 °C) : > 40 mm²/s Partition coefficient n-octanol/water (Log Kow) : Not available Vapour pressure : Not available Vapour pressure at 50°C : Not available : Not available Density $\geq 0.9 - \leq 0.92$ Relative density Relative vapour density at 20°C : Not available Solubility : Not available Particle size : Not applicable

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified Acute toxicity (dermal) : Not classified Acute toxicity (inhalation) : Not classified

butanone; ethyl methyl ketone (78-93-3)

≈ 2193 mg/kg LD50 oral rat

Skin corrosion/irritation Causes skin irritation. Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified

Reproductive toxicity : Suspected of damaging fertility or the unborn child.

STOT-single exposure : May cause drowsiness or dizziness.

butanone; ethyl methyl ketone (78-93-3)

STOT-single exposure May cause drowsiness or dizziness.

NAPHTHA (PETROLEUM), HYDROTREATED LIGHT (64742-49-0)

STOT-single exposure May cause drowsiness or dizziness.

STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.

NAPHTHA (PETROLEUM), HYDROTREATED LIGHT (64742-49-0)

STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Not classified.

VT-239 Clear Nails

Viscosity, kinematic > 40 mm²/s

SECTION 12: Ecological information

12.1. Toxicity

: Harmful to aquatic life with long lasting effects. Ecology - general

Hazardous to the aquatic environment, short-term : Not classified (acute)

: Harmful to aquatic life with long lasting effects.

Hazardous to the aquatic environment, long-term (chronic)

Classification procedure (Hazardous to the aquatic

environment, long-term (chronic))

: Calculation method

12.2. Persistence and degradability

VT-239 Clear Nails		
	Persistence and degradability	Not rapidly degradable

Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

butanone; ethyl methyl ketone (78-93-3)		
Persistence and degradability	Not rapidly degradable	
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT (64742-49-0)		
Persistence and degradability	Not rapidly degradable	
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)		
Persistence and degradability	Not rapidly degradable	

12.3. Bioaccumulative potential

VT-239 Clear Nails	
Bioaccumulative potential	No additional information available

12.4. Mobility in soil

VT-239 Clear Nails	
Mobility in soil	No additional information available

12.5. Other adverse effects

Ozone : Not classified

Other adverse effects : No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transport information

In accordance with UN RTDG / IMDG / IATA

UN RTDG	IMDG	IATA
14.1. UN number		
1133	1133	1133
14.2. UN Proper Shipping Name		
ADHESIVES	ADHESIVES	Adhesives
Transport document description		
UN 1133 ADHESIVES, 3, II	UN 1133 ADHESIVES, 3, II	UN 1133 Adhesives, 3, II
14.3. Transport hazard class(es)		
3	3	3
3	3	3
14.4. Packing group		
II	II	II

Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

UN RTDG	IMDG	IATA
14.5. Environmental hazards		
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available		

14.6. Special precautions for user

UN RTDG

Limited quantities (UN RTDG) : 5L Excepted quantities (UN RTDG) : E2 Packing instruction (UN RTDG) : P001, IBC02 Special packing provisions (UN RTDG) : PP1 Portable tank and bulk container special : T4

instructions (UN RTDG)

Portable tank and bulk container special provisions : TP1, TP8

(UN RTDG)

IMDG

Limited quantities (IMDG) : 5 L Excepted quantities (IMDG) : E2 Packing instructions (IMDG) : P001 : PP1 Special packing provisions (IMDG) IBC packing instructions (IMDG) : IBC02 : T4 Tank instructions (IMDG) : TP1, TP8 Tank special provisions (IMDG)

: F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS EmS-No. (Fire)

: S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS EmS-No. (Spillage)

Stowage category (IMDG)

Properties and observations (IMDG) : Adhesives are solutions of gums, resins, etc., usually volatile due to the solvents. Miscibility

with water depends upon their composition.

IATA

PCA Excepted quantities (IATA) : E2 PCA Limited quantities (IATA) : Y341 PCA limited quantity max net quantity (IATA) : 1L PCA packing instructions (IATA) : 353 PCA max net quantity (IATA) : 5L CAO packing instructions (IATA) : 364 CAO max net quantity (IATA) : 60L Special provisions (IATA) : A3 ERG code (IATA) : 3L

14.7. Transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question

No additional information available

SECTION 16: Other information

Issue date : 1/24/2024 Revision date : 8/26/2025 Supersedes 1/24/2024

Abbreviations and acronyms : CAS-No. - Chemical Abstract Service number

Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

ATE - Acute Toxicity Estimate

EC50 - Median effective concentration

EC-No. - European Community number

IATA - International Air Transport Association

IMDG - International Maritime Dangerous Goods

LC50 - Median lethal concentration

LD50 - Median lethal dose

LOAEL - Lowest Observed Adverse Effect Level

N.O.S. - Not Otherwise Specified

NOAEC - No-Observed Adverse Effect Concentration

NOAEL - No-Observed Adverse Effect Level

NOEC - No-Observed Effect Concentration

OEL - Occupational Exposure Limit

SDS - Safety Data Sheet

Full text of H-statements:	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Asp. Tox. Not classified	Aspiration hazard Not classified
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 4	Flammable liquids, Category 4
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour
H227	Combustible liquid
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

Safety Data Sheet (SDS), UN

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.