



Formulated For The Professionals
Adhesives & Sealants

VT-222 All Purpose Gap Sealant VT-226 GP Gap Sealant

Original Water-based Acrylic Sealant

A versatile, environmentally friendly acrylic sealant for all purpose caulking and sealing applications. It is paintable and has good adhesion to most porous surfaces. It is formulated with the right consistency thus able to withstand pressure during the installation. It is suitable for sealing gaps and joints where slight movements or vibration, if occurred, could cause conventional, non-elastic fillers and putties to crack and fall off. It can be applied smoothly and easily and can be cleaned up with water.

Applications:

General sealing applications: door and window joints, cabinet and wardrobe installation, skirting of wood flooring, etc. Suitable for various substrates: metal, PVC, wood, concrete, gypsum boards, reinforced cement boards, marble, etc.

Applicable Test / Standard:

1. ASTM C920 & ASTM C719, Type S, Grade NS, Class 12.5, Use NT, M
2. Low VOC - USEPA Method 24 and SCAQMD Method 304-91 under SCAQMD Rule 1168

Available colour: White

| Item Code | Content | Carton Quantity |
|-----------|----------------------|-----------------|
| VT-222 | 450 g Cartridge | 24 / Carton |
| VT-226 | 450 g Cartridge (GW) | 24 / Carton |



VT-222

VT-226

Features

- ±12.5 % movement capability (VT-222)
- Paintable
- Economical
- Versatile & permanently flexible
- Easy clean up with water



PARTITION TO WALL GAP



PERIMETER SEALING



GAP BETWEEN WALL & CABINET



WOOD SKIRTING



VITAL TECHNICAL SDN. BHD. (No.: 589221-K)

+603 6094 2088 (Tel) +603 6099 2930 (Fax)

sales@vitaltechnical.com

www.vitaltechnical.com



A member of

