



Formulated For The Professionals

Adhesives & Sealants



uPVC Window

VT-223 Ultra Flex Gap Sealant

High Elastic Acrylic Sealant

VT-223 Ultra Flex Gap Sealant is a premium and highly elastic acrylic sealant, suitable for both external and internal sealing applications. It is formulated with enhanced UV resistance property and can withstand up to ±25% movement. It is paintable and formulated for sealing gaps and joints where high movements or vibrations are expected.

Applications:

It is ideal for external & internal sealing applications. It is good for sealing of building joints that are subject to movement (door and window joints, cabinet and wardrobe installation, skirting of wood flooring, etc.). Suitable for various substrates (metal, PVC, wood, concrete, gypsum boards, reinforced cement boards, marble, etc.).


Applicable Test / Standard:

1. Leadership in Energy and Environmental Design (LEED) v4.1 EQ compliant
2. ASTM C920 & ASTM C719, Type S, Grade NS, Class 25, Use NT, M
3. Low VOC - USEPA Method 24 and SCAQMD Method 304-91 under SCAQMD Rule 1168

Standard Colours: White

Special Colours: Black
(Made-to-Order)

Item Code	Content	Carton Quantity
VT-223	450 g Cartridge	24 / Carton



Features

- ±25% Movement capability
- Exterior & Interior sealant applications
- Paintable
- Permanently flexible
- Easy clean up



PERIMETER SEALING



GAP BETWEEN WALL & CABINET



WOOD SKIRTING



VITAL TECHNICAL SDN. BHD. Co.No.: 200201021558 (589221-K)

+603 6094 2088 (Tel) +603 6099 2930 (Fax)

sales@vitaltechnical.com

www.vitaltechnical.com



A member of

NIPPON PAINT