

A one-component, high performance, paste-like construction adhesive sealant formulated to bond a variety of common construction materials. It has strong initial grab, excellent adhesion and will not slump on vertical surfaces.

## Applications:

Ideal for bonding of skirting boards of wood and PVC, particleboard, masonry, aluminum, galvanized iron, steel, concrete, fibrous cement sheeting, wall brick, concrete, wall panel board and flooring paneling. It is also safe to use on foamed polystyrene and mirror backed tiles.

## Applicable Test / Standard:

- 1. CISCA 2007- Section 6: Pedestal Overturning Moment Test
- Substances of Very High Concern (SVHC) screening.

## Available colour: Brown

Item Code	Content	Carton Quantity
VT-230	350 g Cartridge	24 / Carton







- SVHC compliant
- Mirror and polystyrene safe
- Strong initial grab
- Non-drip paste
- Excellent adhesion on most substrates
- Can be extruded even at low temperatures



VERTICAL BOARDS AND PANELS



WALL PANEL BOARD



WOOD SKIRTING



POLYSTYRENE



## VITAL TECHNICAL SDN. BHD. Co.No.: 200201021558 (589221-K)

- +603 6094 2088 (Tel) +603 6099 2930 (Fax)
- sales@vitaltechnical.com
  - www.vitaltechnical.com







