



VT-232 Eco Nails Construction Adhesive Sealant

Safety Data Sheet

according to the United Nations GHS (Rev. 9, 2021)

Issue date: 8/20/2021 Revision date: 7/23/2022 Supersedes: 7/15/2022 Version: 1.3

SECTION 1: Identification

1.1. GHS Product identifier

Product form : Mixture
Product name : VT-232 Eco Nails Construction Adhesive Sealant
UN-No. (ADR) : 1133
Product group : Trade product

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Sealants
Recommended use : Sealants

1.4. Supplier's details

Manufacturer

Vital Technical Sdn. Bhd.
No.93, Jalan Industri 3/3 Rawang Integrated Industrial Park,
48000 Rawang, Selangor, Malaysia.
T +603 60942088 - F +603 60992930

1.5. Emergency phone number

No additional information available

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification according to the United Nations GHS

Flammable liquids, Category 2	H225	Calculation method
Serious eye damage/eye irritation, Category 2	H319	Calculation method
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336	Calculation method
Hazardous to the aquatic environment – Acute Hazard, Category 3	H402	Calculation method
Hazardous to the aquatic environment – Chronic Hazard, Category 3	H412	Calculation method

Full text of H-statements: see section 16

Adverse physicochemical, human health and environmental effects : Highly flammable liquid and vapour, May cause drowsiness or dizziness, Causes serious eye irritation, Harmful to aquatic life, Harmful to aquatic life with long lasting effects.

2.2. GHS Label elements, including precautionary statements

Labelling according to the United Nations GHS

Hazard pictograms (GHS UN) :



Signal word (GHS UN) : Danger
Hazardous ingredients : HYDROCARBONS, C7-C9, N-ALKANES, ISOALKANES, CYCLICS, methyl acetate
Hazard statements (GHS UN) : H225 - Highly flammable liquid and vapour
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
H412 - Harmful to aquatic life with long lasting effects
Precautionary statements (GHS UN) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.
P233 - Keep container tightly closed.

VT-232 Eco Nails Construction Adhesive Sealant

Safety Data Sheet

according to the United Nations GHS (Rev. 9, 2021)

P240 - Ground and bond container and receiving equipment.
P241 - Use explosion-proof equipment.
P242 - Use non-sparking tools.
P243 - Take action to prevent static discharges.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to the United Nations GHS
methyl acetate	CAS-No.: 79-20-9	10 – 30	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
HYDROCARBONS, C7-C9, N-ALKANES, ISOALKANES, CYCLICS	CAS-No.: 64742-49-0	1 – 10	Flam. Liq. 2, H225 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Full text of H-statements: see section 16

SECTION 4: First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures general : Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Rinse skin with water/shower. Take off immediately all contaminated clothing.
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.
Symptoms/effects after eye contact : Eye irritation.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media : Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Water spray.

5.2. Specific hazards arising from the chemical

Fire hazard : Highly flammable liquid and vapour.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

VT-232 Eco Nails Construction Adhesive Sealant

Safety Data Sheet

according to the United Nations GHS (Rev. 9, 2021)

5.3. Special protective actions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and materials for containment and cleaning up

For containment : Collect spillage.
Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.
Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

methyl acetate (79-20-9)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Methyl acetate
ACGIH TWA (ppm)	200 ppm
ACGIH STEL (ppm)	250 ppm
Remark (ACGIH)	TLV® Basis: Headache; dizziness; nausea; eye dam (degeneration of ganglion cells in the retina)
Regulatory reference	ACGIH 2021

VT-232 Eco Nails Construction Adhesive Sealant

Safety Data Sheet

according to the United Nations GHS (Rev. 9, 2021)

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment (PPE)

Hand protection : Protective gloves
Eye protection : Safety glasses
Skin and body protection : Wear suitable protective clothing
Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s)



8.4. Exposure limit values for the other components

No additional information available

SECTION 9: Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state : Liquid
Appearance : Paste
Colour : light brown.
Odour : Characteristic odour.
Odour threshold : Not available
Melting point : No data available
Freezing point : Not available
Boiling point : > 57 °C
Flammability : Highly flammable liquid and vapour.
Lower explosion limit : Not available
Upper explosion limit : Not available
Flash point : < 23 °C
Auto-ignition temperature : No data available
Decomposition temperature : Not available
pH : No data available
pH solution : Not available
Viscosity, kinematic (calculated value) (40 °C) : > 40 mm²/s
Partition coefficient n-octanol/water (Log Kow) : Not available
Vapour pressure : Not available
Vapour pressure at 50 °C : Not available
Density : Not available
Relative density : ≈ 1.22
Relative vapour density at 20 °C : No data available
Solubility : Not available
Particle size : Not applicable

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour.

VT-232 Eco Nails Construction Adhesive Sealant

Safety Data Sheet

according to the United Nations GHS (Rev. 9, 2021)

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

HYDROCARBONS, C7-C9, N-ALKANES, ISOALKANES, CYCLICS (64742-49-0)

LD50 oral rat	5840 mg/kg
LD50 dermal rat	2920 mg/kg bodyweight

methyl acetate (79-20-9)

LD50 oral rat	≈ 6482 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 Inhalation - Rat	> 49.2 mg/l

Skin corrosion/irritation : Not classified
pH: No data available
Serious eye damage/irritation : Causes serious eye irritation.
pH: No data available
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : May cause drowsiness or dizziness.

HYDROCARBONS, C7-C9, N-ALKANES, ISOALKANES, CYCLICS (64742-49-0)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

methyl acetate (79-20-9)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

STOT-repeated exposure : Not classified
Aspiration hazard : Not classified

VT-232 Eco Nails Construction Adhesive Sealant

Viscosity, kinematic	> 40 mm ² /s
----------------------	-------------------------

HYDROCARBONS, C7-C9, N-ALKANES, ISOALKANES, CYCLICS (64742-49-0)

Animal studies and expert judgment for classification	False
---	-------

VT-232 Eco Nails Construction Adhesive Sealant

Safety Data Sheet

according to the United Nations GHS (Rev. 9, 2021)

methyl acetate (79-20-9)

Animal studies and expert judgment for classification	False
---	-------

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life. Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute) : Harmful to aquatic life.
Classification procedure (Hazardous to the aquatic environment, short-term (acute)) : Calculation method
Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.
Classification procedure (Hazardous to the aquatic environment, long-term (chronic)) : Calculation method

HYDROCARBONS, C7-C9, N-ALKANES, ISOALKANES, CYCLICS (64742-49-0)

LC50 fish 1	3 – 10 mg/l
EC50 other aquatic organisms 1	4.6 – 10 mg/l

12.2. Persistence and degradability

VT-232 Eco Nails Construction Adhesive Sealant

Persistence and degradability	No additional information available
-------------------------------	-------------------------------------

12.3. Bioaccumulative potential

VT-232 Eco Nails Construction Adhesive Sealant

Bioaccumulative potential	No additional information available
---------------------------	-------------------------------------

12.4. Mobility in soil

VT-232 Eco Nails Construction Adhesive Sealant

Mobility in soil	No additional information available
------------------	-------------------------------------

12.5. Other adverse effects

Ozone : Not classified
Other adverse effects : No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transport information



In accordance with UN RTDG / IMDG / IATA

UN RTDG	IMDG	IATA
14.1. UN number		
Not applicable	1133	1133

VT-232 Eco Nails Construction Adhesive Sealant

Safety Data Sheet

according to the United Nations GHS (Rev. 9, 2021)

UN RTDG	IMDG	IATA
14.2. UN Proper Shipping Name		
Not applicable	ADHESIVES	Adhesives
14.3. Transport hazard class(es)		
Not applicable	3	3
Not applicable		
14.4. Packing group		
Not applicable	II	II
14.5. Environmental hazards		
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No
No supplementary information available		

14.6. Special precautions for user

UN RTDG

No data available

IMDG

Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E2
Packing instructions (IMDG) : P001
Special packing provisions (IMDG) : PP1
IBC packing instructions (IMDG) : IBC02
Tank instructions (IMDG) : T4
Tank special provisions (IMDG) : TP1, TP8
EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage) : S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS
Stowage category (IMDG) : B
Properties and observations (IMDG) : Adhesives are solutions of gums, resins, etc., usually volatile due to the solvents. Miscibility with water depends upon their composition.

IATA

PCA Excepted quantities (IATA) : E2
PCA Limited quantities (IATA) : Y341
PCA limited quantity max net quantity (IATA) : 1L
PCA packing instructions (IATA) : 353
PCA max net quantity (IATA) : 5L
CAO packing instructions (IATA) : 364
CAO max net quantity (IATA) : 60L
Special provisions (IATA) : A3
ERG code (IATA) : 3L

14.7. Transport in bulk according to IMO instruments

Not applicable

VT-232 Eco Nails Construction Adhesive Sealant

Safety Data Sheet

according to the United Nations GHS (Rev. 9, 2021)

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question

No additional information available

SECTION 16: Other information

Issue date : 20/08/2021
Revision date : 23/07/2022
Supersedes : 15/07/2022

Full text of H-statements:	
H225	Highly flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H400	Very toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

Safety Data Sheet (SDS), UN

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.