

	<b>VITAL TECHNICAL SDN. BHD.</b>	 
	<b>Technical Data Sheet</b>	
	<b>VT-240 / VT-244 Awning Caulk</b>	

Issuance date: 14/08/09

Revision date: 25/08/2022

Revision No.: 22-01

# VT-240 / VT-244 Awning Caulk

## APPEARANCE

Non-sagging paste

## TOOLING TIME / WORKING TIME

<15 minutes  
(at 25°C & 50% R.H.)

## SKIN-FORM TIME

24 hours

## STANDARD COLOURS

White  
Grey  
Black

## PACKAGING

400 mL/ cartridge  
(24 cartridges/carton)

## VT-244

300 mL/ cartridge  
(24 cartridges/carton)

## SHELF LIFE

24 months

## STORAGE

Store in a dry and cool place with temperature below 30 °C.

## APPLICATION TEMPERATURE

4 °C – 50 °C

## SERVICE TEMPERATURE

-5 °C – 60 °C

## DESCRIPTION



VT-240 Awning Caulk is a one-component, high performance, paste-like sealant formulated to bond a variety of common constructions materials. It has low shrinkage, superior adhesion, outstanding durability, and adheres to most materials without the need for primer.

## TECHNICAL DATA

Curing system	: Oxidizing
Specific Gravity	: 1.50 – 1.60
Solid Content	: 97 – 99%
Max. joint movement	: ±3 %
Shrinkage	: 5 %

## FEATURES

- Outstanding durability
- Weatherproof
- Bonds most materials

## APPLICATION

- Ideal for general sealing applications where only small amount of movement occurs. Well-suited for sealing applications for containers, roofs, external wall, window and door caulking etc. It also exhibits excellent adhesion to metal, wood, glass, zinc, slate, ceramic etc.

## APPLICATION DIRECTION

1. Surfaces must be clean, dry and free of dirt, grease, oil or water.
2. Surfaces should be cleaned with alcohol, M.E.K. or other suitable solvent. Do not use soap or detergent.
3. For a neat finish, apply masking tape and remove it before sealant skins over.
4. Cut nozzle at 45° angle to desired bead-width and apply to substrate with cartridge gun.
5. Tool the sealant within 15 minutes of extrusion.
6. Uncured sealant can be cleaned up with mineral spirits.

## CAUTION

Harmful to aquatic life with long lasting effects. Keep out of reach of children. Safety data sheet available on request. For further health and safety information, consult the latest safety data sheet.

## LEGAL NOTES

Every endeavour has been made to ensure that the information given herein is true and reliable but it is given only for the guidance of our customers. The company cannot accept any responsibility for the loss or damage that may result from the use of the information, due to the possibility of variations of processing or working conditions and of workmanship outside our control. Users are advised to confirm suitability of this product by their own tests.