



Formulated For The Professionals

VT-288 Fire Rated Duct Sealant

Duct Sealant

VT-288 Fire Rated Duct Sealant is a fire resistive, water-based indoor/outdoor air duct sealant. It performs as a tough and flexible adhesive and sealant on the joints and seams, thereby effectively blocks the infiltration of gases, dust and other contaminants and the exfiltration of conditioned air. It is able to accommodate minor vibration and movement, stays flexible and does not crack. It has been tested to meet the requirements for UL94 HB Flammability Test.



Applications:

Ideal for sealing fabricated joints and seams of sheet metal air ducts, fiberglass duct board, thermal insulation, crawl space vapor barriers, house wrap, and other types of air ducts.



Applicable Test / Standard:

1. UL 94 HB. Horizontal Burning Test
2. LEED v4 EQc2 compliant
 - Low VOC Content - USEPA Method 24 and SCAQMD Method 304-91 under SCAQMD Rule 1168
 - Low VOC Emission - CDPH Standard Method v1.2- 2017

Available colour: Grey

Item Code	Content	Carton Quantity
VT-2884K	4.0 kg Pail	4 / Carton
VT-28820K	20.0 kg Pail	-
VT-288	300 ml Cartridge	24 / Carton

Features

- Fire resistive (conforms to UL94 HB)
- Low VOC and low odor
- Excellent workability
- Crack and peel resistant
- Slump resistant
- High solid content



VITAL TECHNICAL SDN. BHD. (No.: 589221-K)

No, 93, Jalan Industri 3/3, Rawang Integrated Industrial Park, 48000 Rawang, Selangor Darul Ehsan, Malaysia.

+603 6094 2088 (Tel) +603 6099 2930 (Fax) sales@vitaltechnical.com

A MEMBER OF THE NIPPON PAINT GROUP

