



*Formulated For The Professionals*  
*Adhesives & Sealants*

# VT-280 Vitalseal

## Small Joint Sealant

VT- 280 is a general purpose, paintable, excellent aging resistance and flexibility sealant used for sealing between aluminium, wood, metal and glass of window joinery. Its unique flow and viscosity characteristic ensure good wetting and sealing of small gaps in aluminium window section without vertical slump problems. However, it is not to use for wide movement or expansion joints. Specially formulated to achieve low VOC, VT- 280 is able to comply to the requirements of SCAQMD rule #1168 for low VOC.

### Applications:

Ideal for sealing of aluminium window with wood, masonry, glass and others, provides waterproof joints with excellent UV resistance.

### Applicable Test / Standard:

1. Low VOC - USEPA Method 24 under SCAQMD rule 1168

**Standard Colours:** Light grey and Dark grey

Item Code	Content	Carton Quantity
VT-280	300 ml Cartridge	24 / Carton
VT-28020L	20.0 L Pail	-



### Features

- Good wetting and sealing of small gaps
- Exterior and interior applications
- Bonds most building materials
- Paintable
- Excellent water & UV resistance



ALUMINIUM WINDOW



**VITAL TECHNICAL SDN. BHD.** Co.No.: 200201021558 (589221-K)

+603 6094 2088 (Tel) +603 6099 2930 (Fax)

sales@vitaltechnical.com

www.vitaltechnical.com



A member of

**NIPPON PAINT**

No, 93, Jalan Industri 3/3, Rawang Integrated Industrial Park, 48000 Rawang, Selangor Darul Ehsan, Malaysia.