

	VITAL TECHNICAL SDN. BHD.	 	Issued date : 21/01/13
	Material Safety Data Sheet		Rev. No. : 5
	601 Black Primer		Revised date : 15/11/17
			Page : 1 of 5

1. Identification of the substance/preparation and of the company/undertaking

Product name : 601 Black Primer
Company : Vital Technical Sdn. Bhd.
 No. 93, Jalan Industri 3/3,
 Rawang Integrated Industrial Park,
 48000 Rawang, Selangor,
 Malaysia.

Telephone : +603 - 6094 2088
Fax : +603 - 6099 2930
Email : sales@vitaltechnical.com
Website : http://www.vitaltechnical.com

2. Hazard(s) identification

GHS Classification

Health	Environmental	Physical
Eye Irrit. 2 STOT SE 3		Flam. Liq. 2



Signal word: Warning

Hazard Statement(s):

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness and dizziness.

Precautionary Statement(s):

P210 Keep away from heat/sparks/open flames/hot surfaces – No smoking.
P242 Use explosion-proof equipment.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing vapours.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P362 Take off contaminated clothing and wash before reuse.

3. Composition/Information on ingredients

Chemical name	CAS No.	EINECS	% (w/w)	Toxicology Data
Ethyl ethanoate	141-78-6	205-500-4	50 - 100	LD₅₀ oral (rat): > 5,000 mg/kg LD₅₀ dermal (rabbit): >18,000 mg/kg LC₅₀ inhalation: >50 mg/L
Butyl ethanoate	123-86-4	204-658-1	10 - 25	LD₅₀ oral (rat): > 8,800 mg/kg LD₅₀ dermal (rabbit): >14,100 mg/kg LC₅₀ inhalation: >20 mg/L
Isocyanate	-	-	< 2.5	LD₅₀ oral (rat): no data LD₅₀ dermal (rabbit): no data LC₅₀ inhalation: no data

4. First-aid measures

	VITAL TECHNICAL SDN. BHD.	  	Issued date : 21/01/13
	Material Safety Data Sheet		Rev. No. : 5
	601 Black Primer		Revised date : 15/11/17
			Page : 2 of 5

Inhalation

Remove to fresh air, keep warm and at rest. Contact physician if discomfort persists.

Skin contact

Remove contaminated clothing. Rinse with copious amount of water. Get medical advice if skin irritation or a rash occurs.

Eye contact

Contact lenses should be removed. Rinse with copious amount of water immediately. Seek medical advice if eye irritation persists.

Ingestion

DO NOT induce vomiting. Drink plenty of water followed by milk if available. Never give anything by mouth to an unconscious person.

5. Fire-fighting measures

Suitable extinguishing media

Use dry chemical powder, foam, carbon dioxide, water fog.

Special fire fighting procedures

Keep up-wind to avoid fumes. Use self-contained breathing apparatus in confined areas.

Unusual fire/explosion hazards

None known.

Thermal decomposition products

Data not available.

Protective measures in fire

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Person-related safety precautions

Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation.

Measure for cleaning/collecting

Absorb with liquid binding material (sand, diatomite, acid binders, universal binders, sawdust, etc). Dispose of contaminated material as waste according to item 13.

Additional information:

Prevent spillage from entering drainage/sewer systems. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

7. Handling and storage

Handling

Ensure good ventilation during processing. Do not eat, drink or smoke while handling.

Protection against fire/explosion

General rules of fire prevention should be observed.

Storage

Keep containers and syringes tightly closed and dry. Store in a well-ventilated area, protected from direct sunlight and heat, with temperature below 30 °C.

8. Exposure controls/personal protection

Industrial hygiene

Remove immediately all contaminated clothing. Do not inhale vapor. Wash hands and contaminated areas with water and soap before leaving the work site. Do not eat, drink or smoke while using the product. Change clothing before leaving workplace and wash before reuse.

Hand protection

	VITAL TECHNICAL SDN. BHD.	 	Issued date : 21/01/13
	Material Safety Data Sheet		Rev. No. : 5
	601 Black Primer		Revised date : 15/11/17
			Page : 3 of 5

Suitable protective gloves like nitrile or viton are recommended. The breakthrough time of the selected glove must be greater than the intended use period.

Respiratory protection

An organic respirator NIOSH-approved for organic vapors is recommended where local ventilation is not adequate.

Eye protection

Protective goggles/safety glasses.

9. Physical and chemical properties

- **Form** : Liquid
- **Color** : Black
- **Odor** : Sweet smell
- **Boiling temperature** : Not determined
- **Flash point** : <21 °C
- **Solubility in water** : Insoluble
- **Specific gravity** : 0.99
- **Vapor density** : <110 kPa at 50 °C

10. Stability and reactivity

Stability and reactivity

Stable when stored under recommended conditions.

Conditions to avoid

Avoid heat, sparks and open flame.

Hazardous decomposition products

During polymerization carbon dioxide will be formed, which in closed containers may result in pressurization. If fire occurs, isocyanates, carbon monoxide, carbon dioxide, nitrogen oxide, hydrogen cyanide, amines and alcohol.

Hazardous polymerization

None known.

Incompatible materials

Contact between ethyl acetate and nitrates, strong oxidizers, strong alkalies, or strong acids may cause fires and explosions. Ethyl acetate reacts vigorously with chlorosulfonic acid, lithium aluminum hydride, 2-chloromethyl furan, oleum, and potassium t-butoxide.

Special Precautions

Ethyl acetate will attack some forms of plastics, rubber, and coatings.

11. Toxicology information

No specific oral, inhalation or dermal toxicology data is known for this product. Any toxicological data included in this section is based on the data associated with the components.

Test	Results
Oral Toxicity	Not classified
Dermal Toxicity	Not classified
Inhalation Toxicity	Not classified
Eye Irritation	Eye irritant, category 2
Dermal Irritation	Not classified
Skin Sensitization	Not classified
Carcinogenicity	Not classified
Reproductive Toxicity	Not classified

12. Ecological information

	VITAL TECHNICAL SDN. BHD.	 	Issued date : 21/01/13
	Material Safety Data Sheet		Rev. No. : 5
	601 Black Primer		Revised date : 15/11/17
			Page : 4 of 5

Ecology toxicity	:	No data available.
Persistence/Degradability	:	Not readily biodegradable.
Bioaccumulative potential	:	No data available.
Mobility	:	No data available.

Individual components of this mixture have been independently tested by the raw material suppliers and any known results have been presented above. The results for the individual components may not be representative of the ecological toxicity of this finished product. This finished product has not been tested to determine individual toxicological/ecological limits. Great caution should be taken to prevent release to the environment. See Section 13 for further information.

13. Disposal information

Waste treatment methods - unused products

Should not be released into the environment. Classified as hazardous waste according to (national equivalent of EC-Dir. 91/689; disposal of toxic and hazardous waste). It must undergo special treatment, e.g. at suitable disposal site, to comply with local regulations. Use a registered waste disposal company and supply accurate information about the nature of the hazard.

Waste disposal number: 08 04 09*

Preferred method of disposal includes incineration under controlled conditions in accordance with all local and national laws and regulations. The generation of waste should be avoided or minimized wherever possible. Untreated material is not suitable for disposal. Waste, even in small quantities, should never be poured down into drains, sewers or watercourses. Waste must be disposed of in accordance with federal, state and local environmental control regulations. This material, when properly mixed and cured at the proper mix ratio, may be safely landfilled.

14. Transport information

Road transport (ADR)

- **Proper shipping name** : PAINT or PAINT RELATED MATERIAL
- **Technical name** : Primer
- **UN number** : UN1263
- **Hazard class** : 2
- **Classification code** : F1
- **Packing group** : PG II

Marine transport (IMDG)

- **Proper shipping name** : PAINT or PAINT RELATED MATERIAL
- **Technical name** : Primer
- **UN number** : UN1263
- **Hazard class** : 2
- **EmS** : F-E, S-E
- **Packing group** : PG II
- **Marine pollutant** : No

Air transport (IATA)

- **Proper shipping name** : PAINT or PAINT RELATED MATERIAL
- **Technical name** : Primer
- **UN number** : UN1263
- **Hazard class** : 9
- **Packing group** : PG II

15. Regulatory information

	VITAL TECHNICAL SDN. BHD.	 	Issued date : 21/01/13
	Material Safety Data Sheet		Rev. No. : 5
	601 Black Primer		Revised date : 15/11/17
			Page : 5 of 5

EU Classification:



F Highly Flammable



Xi Irritant

EU Risk(R) Phrases:

- R11** Highly flammable.
- R36** Irritating to eyes.
- R66** Repeated exposure may cause skin dryness or cracking.
- R67** Vapours may cause drowsiness and dizziness.

EU Safety(S) Phrases:

- S9** Keep container in a well-ventilated area.
- S16** Keep away from sources of ignition - No smoking.
- S23** Do not breathe vapour.
- S26** In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

16. Other information

Definitions:

- **TLV** : Threshold Limit Value.
- **LD₅₀** : The minimum dose required for lethal effects in 50% of a given population of test specimens.
- **NIOSH** : National Institute for Occupational Safety and Health.

All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee these are the only hazards that exist. The details contained herein are based on our present state of knowledge and experience in characterizing our product with regard to any possible safety requirement. We do, however, pass them on without any warranty or property assurances.