




| | | |
|---|----------------------------------|---|
|  | VITAL TECHNICAL SDN. BHD. |   |
| | Technical Data Sheet | |
| | VT-580 Paint Remover | |

Issuance date: 01/11/16

Revision date: 26/04/2023

Revision No.: 23-01

VT-580 Paint Remover

PACKAGING

300 g/ tin
500 g/ tin
(24 tin/ carton)
1.0 kg/ tin
(12 tin/ carton)
3.5 kg/ tin
(6 tin/ carton)

SHELF LIFE

12 months

STORAGE

Store in a dry and cool place with temperature around 30 °C

DESCRIPTION



VT-580 Heavy Duty Paint Remover penetrates into successive coats of paint, varnish or enamel. It is super strong and fast reacting yet non caustic hence will not damage bare surfaces. It is highly viscous and can be applied on vertical surfaces.

TECHNICAL DATA

Principal composition : Blend of highly reactive solvent
Viscosity : 1,200 cPs
Specific gravity : 1.2 ± 0.1

FEATURES

- Non-caustic
- Cost effective
- Super strong and fast reacting
- High viscosity
- Works on vertical surfaces

APPLICATION

Removal of coatings from metal, wood, plaster and glass. Removal of enamel paints, varnishes and bitumens. Can also soften acrylic paints and epoxy paints.

APPLICATION DIRECTION

1. Caution: Product may splash out when removing inner cap.
2. Apply a thick coat onto the painted surfaces with a brush.
3. Leave it for 10 minutes to react with the paint.
4. Remove the softened paint with a paint stripper.
5. Close cap after use and store in cool, dry place.

CAUTION

Contains dichloromethane and methanol. Flammable liquid and vapour. Harmful if swallowed. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer. May cause damage to organs. Obtain special instructions before use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash hands, forearms and face thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. IF exposed or concerned: Call a POISON CENTER or doctor. Keep out of reach of children. Use product outdoors, if possible. If you must use the product indoors, ventilate the area by using a fan and opening all doors and windows. DO NOT use it in an enclosed area with poor ventilation. Safety data sheet available on request. For further health and safety information, consult the latest safety data sheet.

LEGAL NOTES

Every endeavour has been made to ensure that the information given herein is true and reliable but it is given only for the guidance of our customers. The company cannot accept any responsibility for the loss or damage that may result from the use of the information, due to the possibility of variations of processing or working conditions and of workmanship outside our control. Users are advised to confirm suitability of this product by their own tests.

(Scan to learn how to use)



Visit product page:
<http://vitaltechnical.com/product/vt-580-paint-remover/>