



VT-338 AP Contact Adhesive

Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

Issue date: 9/28/2021 Revision date: 11/11/2025 Supersedes: 4/27/2023 Version: 3.1

SECTION 1: Identification

1.1. GHS Product identifier

Product form : Mixture
Product name : VT-338 AP Contact Adhesive
UN-No. (ADR) : 1133
Product group : Trade product

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Adhesives

1.4. Supplier's details

Manufacturer

Vital Technical Sdn. Bhd.
No.93, Jalan Industri 3/3 Rawang Integrated Industrial Park,
48000 Rawang, Selangor, Malaysia.
T +603 60942088 - F +603 60992930

1.5. Emergency phone number

No additional information available

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification according to the United Nations GHS

Flammable liquids, Category 2	H225	On basis of test data
Skin corrosion/irritation, Category 2	H315	Calculation method
Reproductive toxicity, Category 2	H361	Calculation method
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336	Calculation method
Specific target organ toxicity – Repeated exposure, Category 2	H373	Calculation method
Aspiration hazard Not classified		Calculation method
Hazardous to the aquatic environment – Chronic Hazard, Category 3	H412	Calculation method
Full text of H-statements: see section 16		
Adverse physicochemical, human health and environmental effects		: Highly flammable liquid and vapour,Suspected of damaging fertility or the unborn child,May cause damage to organs through prolonged or repeated exposure,May cause drowsiness or dizziness,Causes skin irritation,Harmful to aquatic life with long lasting effects.

2.2. GHS Label elements, including precautionary statements

Labelling according to the United Nations GHS

Hazard pictograms (GHS UN)



Signal word (GHS UN) : Danger
Hazardous ingredients : ethyl acetate; toluene; NAPHTHA (PETROLEUM), HYDROTREATED LIGHT
Hazard statements (GHS UN) : H225 - Highly flammable liquid and vapour
H315 - Causes skin irritation
H336 - May cause drowsiness or dizziness
H361 - Suspected of damaging fertility or the unborn child (Inhalation)
H373 - May cause damage to organs (nervous system, central nervous system) through

VT-338 AP Contact Adhesive

Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

Precautionary statements (GHS UN)	: prolonged or repeated exposure (Inhalation) H412 - Harmful to aquatic life with long lasting effects : P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P103 - Read carefully and follow all instructions. P203 - Obtain, read and follow all safety instructions before use. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed.
-----------------------------------	---

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to the United Nations GHS
toluene	CAS-No.: 108-88-3	50 – 70	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT	CAS-No.: 64742-49-0	1 – 10	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
PHENOL, POLYMER WITH 3-METHYLENE-6-(1-METHYLETHYL)CYCLOHEXENE	CAS-No.: 68240-08-4	1 – 10	Skin Irrit. 2, H315 Eye Irrit. 2, H319
ethyl acetate	CAS-No.: 141-78-6	1 – 10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Full text of H-statements: see section 16

SECTION 4: First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Irritation.

VT-338 AP Contact Adhesive

Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media : Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Water spray.

5.2. Specific hazards arising from the chemical

Fire hazard : Highly flammable liquid and vapour.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective actions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and materials for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.
Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.
Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

VT-338 AP Contact Adhesive

Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ethyl acetate (141-78-6)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Ethyl acetate
IOELV TWA (mg/m ³)	734 mg/m ³
IOELV STEL (mg/m ³)	1468 mg/m ³
IOELV STEL (ppm)	400 ppm
Regulatory reference	COMMISSION DIRECTIVE (EU) 2017/164
USA - ACGIH - Occupational Exposure Limits	
Local name	Ethyl acetate
ACGIH TWA (ppm)	400 ppm
Remark (ACGIH®)	TLV® Basis: URT & eye irr
Regulatory reference	ACGIH 2021
toluene (108-88-3)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Toluene
IOELV TWA (mg/m ³)	192 mg/m ³
IOELV STEL (mg/m ³)	384 mg/m ³
IOELV STEL (ppm)	100 ppm
Notes	Skin
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC
USA - ACGIH - Occupational Exposure Limits	
Local name	Toluene
ACGIH TWA (ppm)	20 ppm
Remark (ACGIH®)	TLV® Basis: CNS, visual & hearing impair; female repro system eff; pregnancy loss. Notations: OTO; A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2021
USA - ACGIH - Biological Exposure Indices	
Local name	TOLUENE
Biological Exposure Indices (BEI)	0.3 mg/g creatinine Parameter: o-Cresol (with hydrolysis) - Medium: urine - Sampling time: End of shift - Notations: B 0.03 mg/l Parameter: Toluene - Medium: urine - Sampling time: End of shift 0.02 mg/l Parameter: Toluene - Medium: blood - Sampling time: Prior to last shift of workweek
Regulatory reference	ACGIH 2021
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT (64742-49-0)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Cyclohexane
IOELV TWA (mg/m ³)	700 mg/m ³
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC

VT-338 AP Contact Adhesive

Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

NAPHTHA (PETROLEUM), HYDROTREATED LIGHT (64742-49-0)		
USA - ACGIH - Occupational Exposure Limits		
Local name	Cyclohexane	
ACGIH TWA (ppm)	100 ppm	
Remark (ACGIH®)	TLV® Basis: CNS impair	
Regulatory reference	ACGIH 2021	
USA - ACGIH - Biological Exposure Indices		
Local name	n-HEXANE	
Biological Exposure Indices (BEI)	0.5 mg/l Parameter: 2,5-Hexanedione (without hydrolysis) - Medium: urine - Sampling time: End of shift	
Regulatory reference	ACGIH 2021	
Exposure limit values for the other components		
n-hexane (110-54-3)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	n-Hexane	
IOELV TWA (mg/m³)	72 mg/m³	
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC	
USA - ACGIH - Occupational Exposure Limits		
Local name	n-Hexane	
ACGIH TWA (ppm)	50 ppm	
Remark (ACGIH®)	TLV® Basis: CNS impair; peripheral neuropathy; eye irr. Notations: Skin; BEI	
Regulatory reference	ACGIH 2021	
USA - ACGIH - Biological Exposure Indices		
Local name	n-HEXANE	
Biological Exposure Indices (BEI)	0.5 mg/l Parameter: 2,5-Hexanedione (without hydrolysis) - Medium: urine - Sampling time: End of shift	
Regulatory reference	ACGIH 2021	
cyclohexane (110-82-7)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	Cyclohexane	
IOELV TWA (mg/m³)	700 mg/m³	
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC	
USA - ACGIH - Occupational Exposure Limits		
Local name	Cyclohexane	
ACGIH TWA (ppm)	100 ppm	
Remark (ACGIH®)	TLV® Basis: CNS impair	
Regulatory reference	ACGIH 2021	

8.2. Appropriate engineering controls

- Appropriate engineering controls : Ensure good ventilation of the work station.
- Environmental exposure controls : Avoid release to the environment.

VT-338 AP Contact Adhesive

Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

8.3. Individual protection measures, such as personal protective equipment (PPE)

Materials for protective clothing :
Hand protection : Protective gloves
Eye protection : Safety glasses
Skin and body protection : Wear suitable protective clothing
Respiratory protection : [In case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s)



8.4. Exposure limit values for the other components

n-hexane (110-54-3)		
EU	Local name	n-Hexane
EU	IOELV TWA (mg/m ³)	72 mg/m ³
USA - ACGIH	Local name	n-Hexane
USA - ACGIH	ACGIH TWA (ppm)	50 ppm
USA - ACGIH	Remark (ACGIH®)	TLV® Basis: CNS impair; peripheral neuropathy; eye irr. Notations: Skin; BEI

cyclohexane (110-82-7)		
EU	Local name	Cyclohexane
EU	IOELV TWA (mg/m ³)	700 mg/m ³
USA - ACGIH	Local name	Cyclohexane
USA - ACGIH	ACGIH TWA (ppm)	100 ppm
USA - ACGIH	Remark (ACGIH®)	TLV® Basis: CNS impair

SECTION 9: Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state : Liquid
Colour : Brown.
Odour : Characteristic.
Odour threshold : Not available
Melting point : Not applicable
Freezing point : Not available
Boiling point : > 68 °C
Flammability : Highly flammable liquid and vapour.
Lower explosion limit : Not available
Upper explosion limit : Not available
Flash point : < 23 °C
Auto-ignition temperature : No data available
Decomposition temperature : Not available
pH : Not applicable
pH solution : Not available
Viscosity, kinematic (calculated value) (40 °C) : > 40 mm²/s
Partition coefficient n-octanol/water (Log Kow) : Not available
Vapour pressure : Not available
Vapour pressure at 50°C : Not available
Density : Not available
Relative density : ≈ 0.9

VT-338 AP Contact Adhesive

Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

Relative vapour density at 20°C	: No data available
Solubility	: Not available
Viscosity, dynamic	: 8000 – 9000 cP
Particle size	: Not applicable

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

PHENOL, POLYMER WITH 3-METHYLENE-6-(1-METHYLETHYL)CYCLOHEXENE (68240-08-4)	
LD50 oral	> 2000 mg/kg
LD50 dermal	> 5000 mg/kg
toluene (108-88-3)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 5000 mg/kg
LC50 Inhalation - Rat	> 20 mg/l/4h

Skin corrosion/irritation	: Causes skin irritation. pH: Not applicable
Serious eye damage/irritation	: Not classified pH: Not applicable
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Suspected of damaging fertility or the unborn child (Inhalation).
STOT-single exposure	: May cause drowsiness or dizziness.

VT-338 AP Contact Adhesive

Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

ethyl acetate (141-78-6)	
STOT-single exposure	May cause drowsiness or dizziness.
toluene (108-88-3)	
STOT-single exposure	May cause drowsiness or dizziness.
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT (64742-49-0)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: May cause damage to organs (nervous system, central nervous system) through prolonged or repeated exposure (Inhalation).
toluene (108-88-3)	
STOT-repeated exposure	May cause damage to organs (central nervous system) through prolonged or repeated exposure (Inhalation).
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT (64742-49-0)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified.
VT-338 AP Contact Adhesive	
Viscosity, kinematic	> 40 mm ² /s

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.
Classification procedure (Hazardous to the aquatic environment, long-term (chronic))	: Calculation method

12.2. Persistence and degradability

VT-338 AP Contact Adhesive	
Persistence and degradability	Not rapidly degradable
PHENOL, POLYMER WITH 3-METHYLENE-6-(1-METHYLETHYL)CYCLOHEXENE (68240-08-4)	
Persistence and degradability	Not rapidly degradable
ethyl acetate (141-78-6)	
Persistence and degradability	Not rapidly degradable
toluene (108-88-3)	
Persistence and degradability	Not rapidly degradable
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT (64742-49-0)	
Persistence and degradability	Not rapidly degradable

12.3. Bioaccumulative potential

VT-338 AP Contact Adhesive	
Bioaccumulative potential	No additional information available

VT-338 AP Contact Adhesive

Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

12.4. Mobility in soil

VT-338 AP Contact Adhesive

Mobility in soil	No additional information available
------------------	-------------------------------------

12.5. Other adverse effects

Ozone : Not classified
Other adverse effects : No additional information available




SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transport information

In accordance with UN RTDG / IMDG / IATA

UN RTDG	IMDG	IATA
14.1. UN number		
1133	1133	1133
14.2. UN Proper Shipping Name		
ADHESIVES (containing flammable liquid)	ADHESIVES (containing flammable liquid)	Adhesives (containing flammable liquid)
Transport document description		
UN 1133 ADHESIVES (containing flammable liquid), 3, II	UN 1133 ADHESIVES (containing flammable liquid), 3, II	UN 1133 Adhesives (containing flammable liquid), 3, II
14.3. Transport hazard class(es)		
3	3	3
		
14.4. Packing group		
II	II	II
14.5. Environmental hazards		
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available		

14.6. Special precautions for user

UN RTDG

Limited quantities (UN RTDG) : 5L
Excepted quantities (UN RTDG) : E2
Packing instruction (UN RTDG) : P001, IBC02
Special packing provisions (UN RTDG) : PP1
Portable tank and bulk container special instructions (UN RTDG) : T4
Portable tank and bulk container special provisions (UN RTDG) : TP1, TP8

VT-338 AP Contact Adhesive

Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

IMDG	
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1, TP8
EmS-No. (Fire)	: F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage)	: S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS
Stowage category (IMDG)	: B
Properties and observations (IMDG)	: Adhesives are solutions of gums, resins, etc., usually volatile due to the solvents. Miscibility with water depends upon their composition.

IATA	
PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y341
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 353
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 364
CAO max net quantity (IATA)	: 60L
Special provisions (IATA)	: A3
ERG code (IATA)	: 3L

14.7. Transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question

No additional information available

SECTION 16: Other information

Issue date	: 9/28/2021
Revision date	: 11/11/2025
Supersedes	: 4/27/2023

Abbreviations and acronyms	: CAS-No. - Chemical Abstract Service number ATE - Acute Toxicity Estimate EC50 - Median effective concentration EC-No. - European Community number IATA - International Air Transport Association IMDG - International Maritime Dangerous Goods LC50 - Median lethal concentration LD50 - Median lethal dose LOAEL - Lowest Observed Adverse Effect Level N.O.S. - Not Otherwise Specified NOAEC - No-Observed Adverse Effect Concentration NOAEL - No-Observed Adverse Effect Level NOEC - No-Observed Effect Concentration OEL - Occupational Exposure Limit SDS - Safety Data Sheet
----------------------------	---

Full text of H-statements:

Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3

VT-338 AP Contact Adhesive

Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

Full text of H-statements:	
Asp. Tox. 1	Aspiration hazard, Category 1
Asp. Tox. Not classified	Aspiration hazard Not classified
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

Safety Data Sheet (SDS), UN

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.