

#### VITAL TECHNICAL SDN. BHD.

#### **Technical Data Sheet**

#### VT-348 Carpet Glue



Brookfield LV2, 20 rpm



Issuance date: 04/01/17 Revision date: 08/05/21 Revision No.: 21-01

## VT-348 Carpet Glue

#### PHYSICAL STATE Yellowish brown

#### PACKAGING 3.0 L/ tin

# (8 tins/carton) OPEN TIME

### 5 to 20 minutes

#### APPLICATION TEMPERATURE

-10 °C to 40 °C

#### SERVICE TEMPERATURE

-10 °C to 60 °C

#### SHELF LIFE 12 months

#### **STORAGE**

Highly flammable, keep away from heat source or naked flames. Store in dry and cool place, below 30 °C.

#### **DESCRIPTION**



VT-348 Carpet Glue is a cost-effective solvent-based adhesive specially formulated for carpet bonding. It is easy to spread and it grabs immediately upon contact. It's easy to use and it offers good bonding strength.

TECHNICAL

Solid content : 27 - 29 %

**DATA** Viscosity at 25°C : 1,400 – 1,700 cPs

Specific gravity : 0.82 – 0.86

**FEATURES** 

- Cost effective
- Specially for carpet bonding
- Excellent adhesion

#### **APPLICATION**

Ideal for carpet bonding, also bonds most other materials such as Formica, rubber, cork, leather, fiberglass, polyurethane foam, EVA to wood, metal or concrete.

## APPLICATION DIRECTION

- 1. Surfaces must be clean, dry and free of dirt, grease, oil or water.
- 2. Stir adhesive before use
- Apply the adhesive to both surfaces to be bonded with a dry, clean brush or scraper to give a uniform coating.
- Allow the solvents to evaporate until the adhesive film is touch dry. It will take between 5 to 20 minutes depending upon surface porosity and weather condition.
- Position the coated surfaces accurately before assemble them. Apply even pressure to consolidate the bond.

#### CAUTION

Highly flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. May cause drowsiness or dizziness. Suspected of damaging fertility. Suspected of damaging the unborn child. (inhalation). May cause damage to organs (nervous system, central nervous system) through prolonged or repeated exposure (inhalation). Toxic to aquatic life with long lasting effects. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Wear protective gloves / protective clothing / eye protection / face protection / hearing protection. Specific treatment. Keep out of reach of children. Safety data sheet available on request. For further health and safety information, consult the latest safety data sheet.

#### **LEGAL NOTES**

Every endeavour has been made to ensure that the information given herein is true and reliable but it is given only for the guidance of our customers. The company cannot accept any responsibility for the loss or damage that may result from the use of the information, due to the possibility of variations of processing or working conditions and of workmanship outside our control. Users are advised to confirm suitability of this product by their own tests.

www.vitaltechnical.com Page 1 of 1