



Formulated For The Professionals

# VT-388 Low VOC Contact Adhesive

## Contact Adhesive

VT-388 is a low VOC (Volatile Organic Compound) compliant synthetic rubber adhesive tested to comply with South Coast Air Quality Management District (SCAQMD) rule 1168. It is easy to spread and it grabs immediately upon contact. It is easy-to-use and offers good bonding strength.

### Applications:

Ideal for bonding of Formica, rubber, cork, leather, fibreglass, polyurethane foam, EVA to wood, metal or concrete. It is also suitable for carpet installation.

### Applicable Test / Standard:

1. Low VOC - USEPA Method 24 SCAQMD Method 303 under SCAQMD rule 1168

Available colour: Yellow



Item Code	Content	Carton Quantity
VT-3881K	1.0 kg Tin	12 / Carton
VT-3883K	3.0 kg Tin	6 / Carton
VT-38815K	15.0 kg Tin	1 / Carton

### Features

- Excellent adhesion
- Bonds most materials
- Green Building application



LAMINATE



CARPET



INSULATION FOR DUCTS & PIPES



**VITAL TECHNICAL SDN. BHD.** (No.: 589221-K)

No, 93, Jalan Industri 3/3, Rawang Integrated Industrial Park, 48000 Rawang, Selangor Darul Ehsan, Malaysia.

+603 6094 2088 (Tel) +603 6099 2930 (Fax)

sales@vitaltechnical.com

A MEMBER OF THE NIPPON PAINT GROUP

