



# VT-145 Vital Steel Epoxy Part A

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830  
Issue date: 31/10/2020 Version: 1.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : VT-145 Vital Steel Epoxy Part A  
Product group : Trade product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Intended for general public  
Main use category : Professional use  
Use of the substance/mixture : Adhesives

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

##### Manufacturer

Vital Technical Sdn. Bhd.  
No.93, Jalan Industri 3/3  
Rawang Integrated Industrial Park,  
48000 Rawang, Selangor, Malaysia.  
T +603 60942088 - F +603 60992930  
[sales@vitaltechnical.com](mailto:sales@vitaltechnical.com)

#### 1.4. Emergency telephone number

No additional information available

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Skin sensitisation, Category 1	H317
Hazardous to the aquatic environment — Chronic Hazard, Category 2	H411

Full text of H statements : see section 16

##### Adverse physicochemical, human health and environmental effects

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07

GHS09

Signal word (CLP) :

Warning

Contains :

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.; bis-[4-(2,3-epoxypropoxy)phenyl]propane

Hazard statements (CLP) :

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

H411 - Toxic to aquatic life with long lasting effects.

# VT-145 Vital Steel Epoxy Part A

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Precautionary statements (CLP) : P101 - If medical advice is needed, have product container or label at hand.  
P102 - Keep out of reach of children.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.  
P321 - Specific treatment (see supplemental first aid instruction on this label).  
P391 - Collect spillage.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
bis-[4-(2,3-epoxipropoxy)phenyl]propane	(CAS-No.) 1675-54-3 (EC-No.) 216-823-5 (EC Index-No.) 603-073-00-2 (REACH-no) 01-2119456619-26	30 – 50	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
TALC	(CAS-No.) 14807-96-6 (EC-No.) 238-877-9	1 – 10	Not classified
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	(CAS-No.) 68609-97-2 (EC-No.) 271-846-8 (EC Index-No.) 603-103-00-4	0.1 – 1	Skin Irrit. 2, H315 Skin Sens. 1, H317

### Specific concentration limits:

Name	Product identifier	Specific concentration limits
bis-[4-(2,3-epoxipropoxy)phenyl]propane	(CAS-No.) 1675-54-3 (EC-No.) 216-823-5 (EC Index-No.) 603-073-00-2 (REACH-no) 01-2119456619-26	( 5 ≤C ≤ 100) Eye Irrit. 2, H319 ( 5 ≤C ≤ 100) Skin Irrit. 2, H315

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.  
First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.  
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.  
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.  
Symptoms/effects after eye contact : Eye irritation.

# VT-145 Vital Steel Epoxy Part A

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.  
Methods for cleaning up : Take up liquid spill into absorbent material.  
Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing dust/fume/gas/mist/vapours/spray.  
Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

### 7.3. Specific end use(s)

No additional information available

# VT-145 Vital Steel Epoxy Part A

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### 8.1.1 National occupational exposure and biological limit values

<b>TALC (14807-96-6)</b>	
<b>Austria - Occupational Exposure Limits</b>	
MAK Daily average value (mg/m <sup>3</sup> )	≈ 2.5 mg/m <sup>3</sup>
<b>Belgium - Occupational Exposure Limits</b>	
Limit value [mg/m <sup>3</sup> ]	≈ 2 mg/m <sup>3</sup>
<b>Denmark - Occupational Exposure Limits</b>	
Grænseværdi (8 timer) (mg/m <sup>3</sup> )	≈ 0.3 mg/m <sup>3</sup>
<b>Hungary - Occupational Exposure Limits</b>	
AK-érték	≈ 2 mg/m <sup>3</sup>
<b>Ireland - Occupational Exposure Limits</b>	
OEL (8 hours ref) (mg/m <sup>3</sup> )	≈ 10 mg/m <sup>3</sup>
<b>Latvia - Occupational Exposure Limits</b>	
OEL TWA (mg/m <sup>3</sup> )	≈ 4 mg/m <sup>3</sup>
<b>Netherlands - Occupational Exposure Limits</b>	
Grenswaarde TGG 8H (mg/m <sup>3</sup> )	≈ 0.25 fibers/cm <sup>3</sup>
<b>Poland - Occupational Exposure Limits</b>	
NDS (mg/m <sup>3</sup> )	≈ 4 mg/m <sup>3</sup>
<b>Spain - Occupational Exposure Limits</b>	
VLA-ED (mg/m <sup>3</sup> )	≈ 2 mg/m <sup>3</sup>
<b>Sweden - Occupational Exposure Limits</b>	
nivågränsvärde (NVG) (mg/m <sup>3</sup> )	≈ 2 mg/m <sup>3</sup>
<b>United Kingdom - Occupational Exposure Limits</b>	
WEL TWA (mg/m <sup>3</sup> )	≈ 1 mg/m <sup>3</sup>
<b>USA - ACGIH - Occupational Exposure Limits</b>	
Local name	Talc
ACGIH TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup> (Containing no asbestos fibers. E - The value is for particulate matter containing no asbestos and < 1 % crystalline silica, R - Respirable particulate matter) 2 mg/m <sup>3</sup> (Containing asbestos fibers. R - Respirable particulate matter)
ACGIH TWA (ppm)	0.1 fibers/cm <sup>3</sup> (Containing asbestos fibers. F - Respirable fibers)
Remark (ACGIH)	Containing no asbestos fibers = TLV® Basis: Pulm fibrosis; pulm func. Notations: A4 Containing asbestos fibers = TLV® Basis: Pneumoconiosis; lung cancer; mesothelioma. Notations: A1 (Confirmed Human Carcinogen)
Regulatory reference	ACGIH 2020

##### **BARIUM SULPHATE PERCIPITATE (7727-43-7)**

<b>Belgium - Occupational Exposure Limits</b>	
Limit value [mg/m <sup>3</sup> ]	≈ 5 mg/m <sup>3</sup>
<b>Ireland - Occupational Exposure Limits</b>	
OEL (8 hours ref) (mg/m <sup>3</sup> )	≈ 5 mg/m <sup>3</sup>

# VT-145 Vital Steel Epoxy Part A

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>BARIUM SULPHATE PERCIPITATE (7727-43-7)</b>	
<b>Latvia - Occupational Exposure Limits</b>	
OEL TWA (mg/m <sup>3</sup> )	≈ 6 mg/m <sup>3</sup>
<b>Spain - Occupational Exposure Limits</b>	
VLA-ED (mg/m <sup>3</sup> )	≈ 10 mg/m <sup>3</sup>
<b>United Kingdom - Occupational Exposure Limits</b>	
WEL TWA (mg/m <sup>3</sup> )	≈ 10 mg/m <sup>3</sup>
<b>USA - ACGIH - Occupational Exposure Limits</b>	
Local name	Barium sulfate
ACGIH TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (I - Inhalable particulate matter, E - The value is for particulate matter containing no asbestos and < 1 % crystalline silica)
Remark (ACGIH)	TLV® Basis: Pneumoconiosis
Regulatory reference	ACGIH 2020

### 8.1.2. Recommended monitoring procedures

No additional information available

### 8.1.3. Air contaminants formed

No additional information available

### 8.1.4. DNEL and PNEC

No additional information available

### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

### 8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



#### 8.2.2.1. Eye and face protection

##### Eye protection:

Safety glasses

#### 8.2.2.2. Skin protection

##### Skin and body protection:

Wear suitable protective clothing

##### Hand protection:

Protective gloves

#### 8.2.2.3. Respiratory protection

# VT-145 Vital Steel Epoxy Part A

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Black.
Odour	: Pleasant.
Odour threshold	: No data available
pH	: Not applicable
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: ≈ 1.96
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

# VT-145 Vital Steel Epoxy Part A

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Skin corrosion/irritation	: Causes skin irritation. pH: Not applicable
Serious eye damage/irritation	: Causes serious eye irritation. pH: Not applicable
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects.
Not rapidly degradable	

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

No additional information available

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

No additional information available

# VT-145 Vital Steel Epoxy Part A

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830






### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

### SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number</b>				
UN 3082	UN 3082	UN 3082	UN 3082	UN 3082
<b>14.2. UN proper shipping name</b>				
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	Environmentally hazardous substance, liquid, n.o.s.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
<b>Transport document description</b>				
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., 9, III, (-)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., 9, III, MARINE POLLUTANT	UN 3082 Environmentally hazardous substance, liquid, n.o.s., 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., 9, III
<b>14.3. Transport hazard class(es)</b>				
9	9	9	9	9
				
<b>14.4. Packing group</b>				
III	III	III	III	III
<b>14.5. Environmental hazards</b>				
Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes
No supplementary information available				

#### 14.6. Special precautions for user

##### Overland transport

Classification code (ADR) : M6  
 Special provisions (ADR) : 274, 335, 375, 601  
 Limited quantities (ADR) : 5I  
 Excepted quantities (ADR) : E1  
 Packing instructions (ADR) : P001, IBC03, LP01, R001  
 Special packing provisions (ADR) : PP1  
 Mixed packing provisions (ADR) : MP19  
 Portable tank and bulk container instructions (ADR) : T4  
 Portable tank and bulk container special provisions (ADR) : TP1, TP29  
 Tank code (ADR) : LGBV  
 Vehicle for tank carriage : AT



# VT-145 Vital Steel Epoxy Part A

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Transport category (ADR) : 3  
Special provisions for carriage - Packages (ADR) : V12  
Special provisions for carriage - Loading, unloading and handling (ADR) : CV13  
Hazard identification number (Kemler No.) : 90  
Orange plates :



Tunnel restriction code (ADR) : -  
EAC code : •3Z

### Transport by sea

Special provisions (IMDG) : 274, 335, 969  
Limited quantities (IMDG) : 5 L  
Excepted quantities (IMDG) : E1  
Packing instructions (IMDG) : LP01, P001  
Special packing provisions (IMDG) : PP1  
IBC packing instructions (IMDG) : IBC03  
Tank instructions (IMDG) : T4  
Tank special provisions (IMDG) : TP1, TP29  
EmS-No. (Fire) : F-A  
EmS-No. (Spillage) : S-F  
Stowage category (IMDG) : A

### Air transport

PCA Excepted quantities (IATA) : E1  
PCA Limited quantities (IATA) : Y964  
PCA limited quantity max net quantity (IATA) : 30kgG  
PCA packing instructions (IATA) : 964  
PCA max net quantity (IATA) : 450L  
CAO packing instructions (IATA) : 964  
CAO max net quantity (IATA) : 450L  
Special provisions (IATA) : A97, A158, A197  
ERG code (IATA) : 9L

### Inland waterway transport

Classification code (ADN) : M6  
Special provisions (ADN) : 274, 335, 375, 601  
Limited quantities (ADN) : 5 L  
Excepted quantities (ADN) : E1  
Equipment required (ADN) : PP  
Number of blue cones/lights (ADN) : 0

### Rail transport

Classification code (RID) : M6  
Special provisions (RID) : 274, 335, 375, 601  
Limited quantities (RID) : 5L  
Excepted quantities (RID) : E1  
Packing instructions (RID) : P001, IBC03, LP01, R001  
Special packing provisions (RID) : PP1  
Mixed packing provisions (RID) : MP19  
Portable tank and bulk container instructions (RID) : T4  
Portable tank and bulk container special provisions (RID) : TP1, TP29  
Tank codes for RID tanks (RID) : LGBV  
Transport category (RID) : 3  
Special provisions for carriage – Packages (RID) : W12  
Special provisions for carriage - Loading, unloading and handling (RID) : CW13, CW31  
Colis express (express parcels) (RID) : CE8  
Hazard identification number (RID) : 90

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

# VT-145 Vital Steel Epoxy Part A

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

##### 15.1.2. National regulations

###### Germany

Employment restrictions : Observe restrictions according Act on the Protection of Working Mothers (MuSchG)  
Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG)

Water hazard class (WGK) : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1)

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

###### Netherlands

ABM category : A(2) - toxic for aquatic organisms, may have longterm hazardous effects in aquatic environment

SZW-lijst van kankerverwekkende stoffen : oxirane, mono[(C12-14-alkyloxy)methyl] derivs. is listed

SZW-lijst van mutagene stoffen : oxirane, mono[(C12-14-alkyloxy)methyl] derivs. is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : None of the components are listed

###### Denmark

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

### SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BLV	Biological limit value
CAS-No.	Chemical Abstract Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
EC-No.	European Community number
EN	European Standard
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods

# VT-145 Vital Steel Epoxy Part A

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative
WGK	Water Hazard Class

Full text of H- and EUH-statements:	
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.