



# VT-146 / VT-148 /VT-149 Rapid 3 Ton 4 Minutes Epoxy Part B

## Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

Issue date: 10/4/2021 Revision date: 3/25/2026 Supersedes: 4/15/2022 Version: 2.1

### SECTION 1: Identification

#### 1.1. GHS Product identifier

Product form : Mixture  
Product name : VT-146 / VT-148 /VT-149 Rapid 3 Ton 4 Minutes Epoxy Part B  
Product group : Trade product

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Recommended use : Adhesives

#### 1.4. Supplier's details

##### Manufacturer

Vital Technical Sdn. Bhd.  
No.93, Jalan Industri 3/3 Rawang Integrated Industrial Park,  
48000 Rawang, Selangor, Malaysia.  
T +603 60942088 - F +603 60992930

#### 1.5. Emergency phone number

No additional information available

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

##### Classification according to the United Nations GHS

Skin corrosion/irritation, Category 3	H316	Calculation method
Skin sensitisation, Category 1	H317	Calculation method
Hazardous to the aquatic environment – Acute Hazard, Category 3	H402	Calculation method
Hazardous to the aquatic environment – Chronic Hazard, Category 3	H412	Calculation method

Full text of H-statements: see section 16

Adverse physicochemical, human health and environmental effects : May cause an allergic skin reaction,Harmful to aquatic life with long lasting effects.

#### 2.2. GHS Label elements, including precautionary statements

##### Labelling according to the United Nations GHS

Hazard pictograms (GHS UN) :



Signal word (GHS UN) : Warning  
Hazardous ingredients : POLY[OXY(METHYL-1,2-ETHANEDIYL)], .ALPHA.-HYDRO.-OMEGA.-HYDROXY-, ETHER WITH 2,2-BIS(HYDROXYMETHYL)-1,3-PROPANEDIOL(4:1), 2-HYDROXY-3-MERCAPTOPROPYL ETHER  
Hazard statements (GHS UN) : H316 - Causes mild skin irritation  
H317 - May cause an allergic skin reaction  
H412 - Harmful to aquatic life with long lasting effects  
Precautionary statements (GHS UN) : P101 - If medical advice is needed, have product container or label at hand.  
P102 - Keep out of reach of children.  
P103 - Read carefully and follow all instructions.  
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

# VT-146 / VT-148 /VT-149 Rapid 3 Ton 4 Minutes Epoxy Part B

## Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

P272 - Contaminated work clothing should not be allowed out of the workplace.  
P273 - Avoid release to the environment.

### 2.3. Other hazards which do not result in classification

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to the United Nations GHS
POLY[OXY(METHYL-1,2-ETHANEDIYL)], .ALPHA.-HYDRO.-OMEGA.-HYDROXY-, ETHER WITH 2,2-BIS(HYDROXYMETHYL)-1,3-PROPANEDIOL(4:1), 2-HYDROXY-3-MERCAPTOPROPYL ETHER	CAS-No.: 72244-98-5	≥ 90	Skin Sens. 1B, H317 Aquatic Chronic 3, H412
1,3-BIS[3-(DIMETHYLAMINO)PROPYL]UREA	CAS-No.: 52338-87-1	1 – 10	Skin Irrit. 2, H315 Eye Irrit. 2, H319

Full text of H-statements: see section 16

## SECTION 4: First-aid measures

### 4.1. Description of necessary first-aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.  
First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.  
First-aid measures after eye contact : Rinse eyes with water as a precaution.  
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after skin contact : May cause an allergic skin reaction.

### 4.3. Indication of immediate medical attention and special treatment needed, if necessary

Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

### 5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.3. Special protective actions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

# VT-146 / VT-148 /VT-149 Rapid 3 Ton 4 Minutes Epoxy Part B

## Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

##### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and materials for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.  
Other information : Dispose of materials or solid residues at an authorized site.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Wear personal protective equipment.  
Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

No additional information available

#### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

#### 8.3. Individual protection measures, such as personal protective equipment (PPE)

Materials for protective clothing :  
Hand protection : Protective gloves  
Eye protection : Safety glasses  
Skin and body protection : Wear suitable protective clothing  
Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment

##### Personal protective equipment symbol(s)



#### 8.4. Exposure limit values for the other components

No additional information available

# VT-146 / VT-148 /VT-149 Rapid 3 Ton 4 Minutes Epoxy Part B

## Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

### SECTION 9: Physical and chemical properties

#### 9.1. Basic physical and chemical properties

Physical state	: Liquid
Colour	: Colourless.
Odour	: nauseating.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Non flammable
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: Not available
Auto-ignition temperature	: Not applicable
Decomposition temperature	: Not available
pH	: Not applicable
pH solution	: Not available
Viscosity, kinematic (calculated value) (40 °C)	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: 1.16
Relative vapour density at 20°C	: Not applicable
Solubility	: Not available
Particle size	: Not applicable

#### 9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

#### 10.5. Incompatible materials

No additional information available

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified

# VT-146 / VT-148 /VT-149 Rapid 3 Ton 4 Minutes Epoxy Part B

## Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

Acute toxicity (inhalation) : Not classified

### 1,3-BIS[3-(DIMETHYLAMINO)PROPYL]UREA (52338-87-1)

LD50 oral	5000 mg/kg
-----------	------------

Skin corrosion/irritation : Causes mild skin irritation.  
pH: Not applicable

Serious eye damage/irritation : Not classified  
pH: Not applicable

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term (acute) : Harmful to aquatic life.

Classification procedure (Hazardous to the aquatic environment, short-term (acute)) : Calculation method

Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

Classification procedure (Hazardous to the aquatic environment, long-term (chronic)) : Calculation method

### 12.2. Persistence and degradability

#### VT-146 / VT-148 /VT-149 Rapid 3 Ton 4 Minutes Epoxy Part B

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

#### 1,3-BIS[3-(DIMETHYLAMINO)PROPYL]UREA (52338-87-1)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

#### POLY[OXY(METHYL-1,2-ETHANEDIYL)], .ALPHA.-HYDRO-.OMEGA.-HYDROXY-, ETHER WITH 2,2-BIS(HYDROXYMETHYL)-1,3-PROPANEDIOL(4:1), 2-HYDROXY-3-MERCAPTOPROPYL ETHER (72244-98-5)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

### 12.3. Bioaccumulative potential

#### VT-146 / VT-148 /VT-149 Rapid 3 Ton 4 Minutes Epoxy Part B

Bioaccumulative potential	No additional information available
---------------------------	-------------------------------------

### 12.4. Mobility in soil

#### VT-146 / VT-148 /VT-149 Rapid 3 Ton 4 Minutes Epoxy Part B

Mobility in soil	No additional information available
------------------	-------------------------------------

### 12.5. Other adverse effects

Ozone : Not classified

Other adverse effects : No additional information available

# VT-146 / VT-148 /VT-149 Rapid 3 Ton 4 Minutes Epoxy Part B

## Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)


### SECTION 13: Disposal considerations

#### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

### SECTION 14: Transport information

In accordance with UN RTDG / IMDG / IATA

UN RTDG	IMDG	IATA
<b>14.1. UN number</b>		
Not applicable	Not regulated	3334
<b>14.2. UN Proper Shipping Name</b>		
Not applicable	Not regulated	Aviation regulated liquid, n.o.s. (MERCAPTAN-TERMINATED POLMER)
<b>Transport document description</b>		
Not applicable	Not regulated	UN 3334 Aviation regulated liquid, n.o.s. (MERCAPTAN-TERMINATED POLMER), 9, III
<b>14.3. Transport hazard class(es)</b>		
Not applicable	Not regulated	9
Not applicable	Not regulated	
<b>14.4. Packing group</b>		
Not applicable	Not regulated	III
<b>14.5. Environmental hazards</b>		
Not applicable	Not regulated	Dangerous for the environment: No
No supplementary information available		

#### 14.6. Special precautions for user

##### UN RTDG

Not applicable

##### IMDG

Not regulated

##### IATA

PCA Excepted quantities (IATA) : E1  
PCA Limited quantities (IATA) : Y964  
PCA limited quantity max net quantity (IATA) : 30kgG  
PCA packing instructions (IATA) : 964  
PCA max net quantity (IATA) : 100L  
CAO packing instructions (IATA) : 964  
CAO max net quantity (IATA) : 220L  
Special provisions (IATA) : A27  
ERG code (IATA) : 9A

#### 14.7. Transport in bulk according to IMO instruments

Not applicable

# VT-146 / VT-148 /VT-149 Rapid 3 Ton 4 Minutes Epoxy Part B

## Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations specific for the product in question

No additional information available

### SECTION 16: Other information

Issue date : 10/4/2021  
Revision date : 3/25/2026  
Supersedes : 4/15/2022

Abbreviations and acronyms : ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road  
ATE - Acute Toxicity Estimate  
BLV - Biological limit value  
CAS-No. - Chemical Abstract Service number  
CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008  
DMEL - Derived Minimal Effect level  
DNEL - Derived-No Effect Level  
EC50 - Median effective concentration  
EC-No. - European Community number  
EN - European Standard  
IATA - International Air Transport Association  
IMDG - International Maritime Dangerous Goods  
LC50 - Median lethal concentration  
LD50 - Median lethal dose  
LOAEL - Lowest Observed Adverse Effect Level  
NOAEC - No-Observed Adverse Effect Concentration  
NOAEL - No-Observed Adverse Effect Level  
NOEC - No-Observed Effect Concentration  
OEL - Occupational Exposure Limit  
PBT - Persistent Bioaccumulative Toxic  
PNEC - Predicted No-Effect Concentration  
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006  
RID - Regulations concerning the International Carriage of Dangerous Goods by Rail  
SDS - Safety Data Sheet  
vPvB - Very Persistent and Very Bioaccumulative  
WGK - Water Hazard Class  
N.O.S. - Not Otherwise Specified

#### Full text of H-statements:

Aquatic Acute 3	Hazardous to the aquatic environment – Acute Hazard, Category 3
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Irrit. 3	Skin corrosion/irritation, Category 3
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B
H315	Causes skin irritation
H316	Causes mild skin irritation
H317	May cause an allergic skin reaction

# VT-146 / VT-148 /VT-149 Rapid 3 Ton 4 Minutes Epoxy Part B

## Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

Full text of H-statements:	
H319	Causes serious eye irritation
H402	Harmful to aquatic life
H412	Harmful to aquatic life with long lasting effects

Safety Data Sheet (SDS), UN

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.