



Formulated For The Professionals

VT-138 / VT-195 Rapid Steel Putty

Epoxy Adhesive & Putty

A hand-mixable, steel-reinforced, epoxy putty that mixes in just one minute to provide fast repairs to items made of ferrous and aluminium metals. It comes in a handy "tootsie-roll" form, contains pre-measured portions of activator and base throughout with the curing agent (activator) encapsulated in the consistency eliminates drips and runs, providing "no mess" applications with no tools required for use. It cures to a dark grey metallic colour. Once cured, it can be tapped, drilled, screwed, sawed, machined, ground, filed or painted. It will not rust, shrink or pull away. It is resistant to water, temperature extremes, and chemicals such as hydrocarbons, ketones, alcohols, esters, halocarbons, aqueous salt solutions and dilute acids and bases.

Applications:

Ideal to repair ferrous metals, rebuild small engine parts, fill cracks and voids in metals, seal leaks, form nuts & bolts, repair stripped threads, form anchor machines, repair metal tools, equipment ducts, pipes, housing & appliances, sink traps and auto bodies. Also bonds to wood, glass, masonry and many plastics. Suitable for interior and exterior use.

Available colour: Dark grey

Item Code	Content	Inner Box	Carton Quantity
VT-138	50 g / Pack	12	144 / Carton
VT-13850	50 g / Tube	24	288 / Carton
VT-138100	100 g / Tube	12	144 / Carton
VT-195	28.4 g (1 oz.) / Pack	12	144 / Carton



Features

- Fast setting
- Work on all metals
- Paintable
- Instant bonding and superior strength



RADIATOR



STEEL PIPE



VITAL TECHNICAL SDN. BHD. (No.: 589221-K)

No, 93, Jalan Industri 3/3, Rawang Integrated Industrial Park, 48000 Rawang, Selangor Darul Ehsan, Malaysia.

+603 6094 2088 (Tel) +603 6099 2930 (Fax)

sales@vitaltechnical.com

A MEMBER OF THE NIPPON PAINT GROUP

