

A medium setting (30 minutes), fiberglass-reinforced polymer compound that enables permanent repairs to many surfaces including fiberglass, concrete, ceramic, glass, metals, wood and many plastics. It is specially formulated to adhere to surfaces exposed to damp, wet or underwater (salt or fresh) conditions. Each handy stick contains premeasured portions

of activator and base throughout – no measuring or mixing tools are necessary. It contains a fading blue dye and becomes white after mixing. The consistency (like modelling clay) eliminates drips and runs, facilitates adhesion to the substrate and allows the material to be shaped and formed as needed before curing begins. Once cured, it can be drilled, screwed, filed, carved, sanded or painted. It will not shrink or pull away. It is resistant to water, temperature extremes, and chemicals such as hydrocarbons, ketones, alcohols, esters, halocarbons, aqueous salt solutions and dilute acids and bases.

Aguatix

Pucks

Pucks

Aguat

Maguat

M



Applications: After proper mixing, the epoxy putty molds like clay and may be used to patch dings, scratches, cuts, gouges, and rebuild holes in fiberglass, metal, and wooden boat decks and hulls; to repair fittings, pipes, electrical connections, leaking gaskets, water tanks, fish boxes, marine recreational equipments, tubs, battery cases, sinks, spas, hot tubs, gutters, tanks, pools; to form custom gaskets. It is ideal for repairs to damp wet areas and underwater applications; cures to fiberglass white color. Suitable for interior and exterior use.

Applicable Test / Standard:

- 1. RoSH Directive 2011/65/EU
- 2. SVHC compliant.

Available colour: White

٠.					
	Item Code	Content	Inner Box	Carton Quantity	
	VT-139	50 g / Pack	12	144 / Carton	
	VT-13950	50 g / Tube	24	288 / Carton	
	VT-139100	100 g / Tube	12	144 / Carton	
	VT-196	28.4 g (1 oz.) / Pack	12	144 / Carton	

Features

- Bond in 30 minutes
- Work on wet surface
- Easy to use








OIL TANK



VITAL TECHNICAL SDN. BHD. (No.: 589221-K)

No, 93, Jalan Industri 3/3, Rawang Integrated Industrial Park, 48000 Rawang, Selangor Darul Ehsan, Malaysia.



(Fax)

sales@vitaltechnical.com







