



Formulated For The Professionals

VT-510 All Purpose Structural Epoxy

Epoxy Adhesive

All Purpose Structural Epoxy is a two-component epoxy designed to form a tough adhesive material that is resistant to weathering, fungus, seawater, decay, gasoline, alkali, and even certain acids. It exhibits a remarkable combination of properties: high mechanical strength, excellent resistance to most chemicals, and high heat resistance. It contains no solvent that causes shrinkage, chipping, peeling off, or cracking. It allows easy workability and bonding to most surfaces.



Applications:

It is specially formulated for heavy duty bonding and repair applications, where increased strength, durability and reliability are required. It works well on fiberglass, glass, wood, metal, concrete and most plastics.

Available colour: Light red

Properties:

- Light red cured colour
- 1:1 Mixing ratio by volume
- 45 minutes working time (Pot life)
- 90 minutes set time
- 6 hours to handling strength
- 24 hours to full strength

Item Code	Content	Carton Quantity
VT-510300	300 g Cans Set	50 Sets / Carton
VT-510700	700 g Cans Set	24 Sets / Carton
VT-5101K4	1.40 kg Cans Set	12 Sets / Carton
VT-5102K8	2.80 kg Cans Set	6 Sets / Carton

Features

- High mechanical strength
- Excellent resistance to most chemicals
- Good weathering resistance
- High temperature resistance
- Does not shrink, chip, peel, or crack



RESIN | HARDENER



CURED



WOODEN BOAT



WOOD FURNITURE



VITAL TECHNICAL SDN. BHD. (No.: 589221-K)

No, 93, Jalan Industri 3/3, Rawang Integrated Industrial Park, 48000 Rawang, Selangor Darul Ehsan, Malaysia.

+603 6094 2088 (Tel) +603 6099 2930 (Fax) sales@vitaltechnical.com

A MEMBER OF THE NIPPON PAINT GROUP

