



# VT-511 Non-Sag Epoxy Part B

## Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

Issue date: 12/9/2021 Revision date: 9/5/2022 Supersedes: 12/9/2021 Version: 1.1

### SECTION 1: Identification

#### 1.1. GHS Product identifier

Product form : Mixture  
Product name : VT-511 Non-Sag Epoxy Part B

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

No additional information available

#### 1.4. Supplier's details

##### Manufacturer

Vital Technical Sdn. Bhd.  
No.93, Jalan Industri 3/3 Rawang Integrated Industrial Park,  
48000 Rawang, Selangor, Malaysia.  
T +603 60942088 - F +603 60992930

#### 1.5. Emergency phone number

No additional information available

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

##### Classification according to the United Nations GHS

Skin corrosion/irritation, Category 2	H315	Calculation method
Serious eye damage/eye irritation, Category 1	H318	Calculation method
Respiratory sensitisation, Category 1	H334	Calculation method
Skin sensitisation, Category 1	H317	Calculation method
Hazardous to the aquatic environment – Chronic Hazard, Category 3	H412	Calculation method

Full text of H-statements: see section 16

Adverse physicochemical, human health and environmental effects : Causes skin irritation, May cause an allergic skin reaction, Causes serious eye damage, May cause allergy or asthma symptoms or breathing difficulties if inhaled, Harmful to aquatic life with long lasting effects.

#### 2.2. GHS Label elements, including precautionary statements

##### Labelling according to the United Nations GHS

Hazard pictograms (GHS UN) :



Signal word (GHS UN) : Danger

Hazardous ingredients : 2,2'-IMINODIETHYLAMINE; 1,2-DIAMINOETHANE; FATTY ACIDS, C18-UNSATD., DIMERS, POLYMERS WITH TALL-OIL FATTY ACIDS AND TRIETHYLENETETRAMINE; N,N'-BIS(3-AMINOPROPYL)ETHYLENEDIAMINE; 3,6-diazaoctanethylenediamin; triethylenetetramine

Hazard statements (GHS UN) : H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H318 - Causes serious eye damage  
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled  
H412 - Harmful to aquatic life with long lasting effects

Precautionary statements (GHS UN) : P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.  
P264 - Wash hands, forearms and face thoroughly after handling.

# VT-511 Non-Sag Epoxy Part B

## Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

P264+P265 - Wash hands, forearms and face thoroughly after handling. Do not touch eyes.  
P272 - Contaminated work clothing should not be allowed out of the workplace.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection.

### 2.3. Other hazards which do not result in classification

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to the United Nations GHS
FATTY ACIDS, C18-UNSATD.,DIMERS,POLYMERS WITH TALL-OIL FATTY ACIDS AND TRIETHYLENETETRAMINE	CAS-No.: 68082-29-1	1 – 10	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 2, H411
BENZYL ALCOHOL	CAS-No.: 100-51-6	1 – 10	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2, H319
2,2'-IMINODIETHYLAMINE	CAS-No.: 111-40-0	1 – 10	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Corr. 1B, H314 Skin Sens. 1, H317
N,N'-BIS(3-AMINOPROPYL)ETHYLENEDIAMINE	CAS-No.: 10563-26-5	0.1 – 1	Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317
3,6-diazaoctanethylenediamin; triethylenetetramine	CAS-No.: 112-24-3	0.1 – 1	Acute Tox. 4 (Dermal), H312 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Chronic 3, H412
1,2-DIAMINOETHANE	CAS-No.: 107-15-3	0.1 – 1	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Corr. 1B, H314 Resp. Sens. 1, H334 Skin Sens. 1, H317

Full text of H-statements: see section 16

## SECTION 4: First-aid measures

### 4.1. Description of necessary first-aid measures

First-aid measures general	: Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a poison center or a doctor.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

# VT-511 Non-Sag Epoxy Part B

## Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

### 4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Serious damage to eyes.

### 4.3. Indication of immediate medical attention and special treatment needed, if necessary

Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

### 5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.3. Special protective actions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and materials for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.  
Other information : Dispose of materials or solid residues at an authorized site.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing dust/fume/gas/mist/vapours/spray.  
Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

# VT-511 Non-Sag Epoxy Part B

## Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

No additional information available

#### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

#### 8.3. Individual protection measures, such as personal protective equipment (PPE)

Hand protection : Protective gloves  
Eye protection : Safety glasses  
Skin and body protection : Wear suitable protective clothing  
Respiratory protection : [In case of inadequate ventilation] wear respiratory protection.

#### Personal protective equipment symbol(s)



#### 8.4. Exposure limit values for the other components

No additional information available

### SECTION 9: Physical and chemical properties

#### 9.1. Basic physical and chemical properties

Physical state : Liquid  
Appearance : Paste  
Colour : Beige.  
Odour : Not available  
Odour threshold : Not available  
Melting point : Not applicable  
Freezing point : Not available  
Boiling point : Not available  
Flammability : Non flammable.  
Lower explosion limit : Not available  
Upper explosion limit : Not available  
Flash point : Not available  
Auto-ignition temperature : Not available  
Decomposition temperature : Not available  
pH : Not available  
pH solution : Not available  
Viscosity, kinematic (calculated value) (40 °C) : Not available  
Partition coefficient n-octanol/water (Log Kow) : Not available  
Vapour pressure : Not available  
Vapour pressure at 50 °C : Not available  
Density : Not available  
Relative density : 1.85  
Relative vapour density at 20 °C : Not available  
Solubility : Not available  
Particle size : Not applicable

#### 9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

# VT-511 Non-Sag Epoxy Part B

## Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

#### 10.5. Incompatible materials

No additional information available

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitisation	: May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general	: Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.
Classification procedure (Hazardous to the aquatic environment, long-term (chronic))	: Calculation method

#### 12.2. Persistence and degradability

##### VT-511 Non-Sag Epoxy Part B

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

# VT-511 Non-Sag Epoxy Part B

## Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

<b>2,2'-IMINODIETHYLAMINE (111-40-0)</b>	
Persistence and degradability	Not rapidly degradable
<b>1,2-DIAMINOETHANE (107-15-3)</b>	
Persistence and degradability	Not rapidly degradable
<b>FATTY ACIDS, C18-UNSATD.,DIMERS,POLYMERS WITH TALL-OIL FATTY ACIDS AND TRIETHYLENETETRAMINE (68082-29-1)</b>	
Persistence and degradability	Not rapidly degradable
<b>N,N'-BIS(3-AMINOPROPYL)ETHYLENEDIAMINE (10563-26-5)</b>	
Persistence and degradability	Not rapidly degradable
<b>BENZYL ALCOHOL (100-51-6)</b>	
Persistence and degradability	Not rapidly degradable
<b>3,6-diazaoctanethylenediamin; triethylenetetramine (112-24-3)</b>	
Persistence and degradability	Not rapidly degradable

### 12.3. Bioaccumulative potential

<b>VT-511 Non-Sag Epoxy Part B</b>	
Bioaccumulative potential	No additional information available

### 12.4. Mobility in soil

<b>VT-511 Non-Sag Epoxy Part B</b>	
Mobility in soil	No additional information available

### 12.5. Other adverse effects

Ozone : Not classified  
Other adverse effects : No additional information available

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

## SECTION 14: Transport information

In accordance with UN RTDG / IMDG / IATA

UN RTDG	IMDG	IATA
<b>14.1. UN number</b>		
Not applicable	Not applicable	Not applicable
<b>14.2. UN Proper Shipping Name</b>		
Not applicable	Not applicable	Not applicable
<b>14.3. Transport hazard class(es)</b>		
Not applicable	Not applicable	Not applicable
<b>14.4. Packing group</b>		
Not applicable	Not applicable	Not applicable

# VT-511 Non-Sag Epoxy Part B

## Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

UN RTDG	IMDG	IATA
<b>14.5. Environmental hazards</b>		
Not applicable	Not applicable	Not applicable
No supplementary information available		

### 14.6. Special precautions for user

#### UN RTDG

Not applicable

#### IMDG

Not applicable

#### IATA

Not applicable

### 14.7. Transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations specific for the product in question

No additional information available

## SECTION 16: Other information

Issue date : 12/9/2021  
Revision date : 9/5/2022  
Supersedes : 12/9/2021

Abbreviations and acronyms : CAS-No. - Chemical Abstract Service number  
ATE - Acute Toxicity Estimate  
EC50 - Median effective concentration  
EC-No. - European Community number  
IATA - International Air Transport Association  
IMDG - International Maritime Dangerous Goods  
LC50 - Median lethal concentration  
LD50 - Median lethal dose  
LOAEL - Lowest Observed Adverse Effect Level  
N.O.S. - Not Otherwise Specified  
NOAEC - No-Observed Adverse Effect Concentration  
NOAEL - No-Observed Adverse Effect Level  
NOEC - No-Observed Effect Concentration  
OEL - Occupational Exposure Limit  
SDS - Safety Data Sheet

Full text of H-statements:	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Eye Dam. 1	Serious eye damage/eye irritation, Category 1

# VT-511 Non-Sag Epoxy Part B

## Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

Full text of H-statements:	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Resp. Sens. 1	Respiratory sensitisation, Category 1
Skin Corr. 1B	Skin corrosion/irritation, Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
H226	Flammable liquid and vapour
H302	Harmful if swallowed
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

Safety Data Sheet (SDS), UN

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.