



Formulated For The Professionals

# VT-511 Non Sag Epoxy

## Epoxy Adhesive

Non-Sag Epoxy is formulated as a putty-like mastic with non-flowing consistency. It is also capable of curing underwater, making it suitable for boat building and repair applications. The non-sag property allows it to perform well on vertical and overhead applications of up to maximum 1/2 inch gap. It is able to resist to weathering, fungus, seawater, decay, gasoline, alkalis, and even some acids.



### Applications:

It is suitable for various bonding, sealing, gap filling and repair applications where the non-sag property is required. It helps to increase the strength, durability and reliability in most conditions. It is good on fiberglass, glass, wood, metal, concrete and many plastics.

Available colour: Yellow Ochre

### Properties:

- Yellow ochre cured colour
- 1:1 Mixing ratio by volume
- 45 minutes working time
- 90 minutes set time
- 6 hours to handling strength
- 72 hours to full strength

Item Code	Content	Carton Quantity
VT-511300	300 g Cans Set	50 Sets / Carton
VT-511700	700 g Cans Set	24 Sets / Carton
VT-5111K4	1.40 kg Cans Set	12 Sets / Carton
VT-5112K8	2.80 kg Cans Set	6 Sets / Carton

### Features

- High mechanical strength
- Excellent resistance to most chemicals
- Good weathering resistance
- High temperature resistance
- Does not shrink, chip, peel, or crack



RESIN | HARDENER



CURED



WOODEN DOOR



WOOD FURNITURE



VITAL TECHNICAL SDN. BHD. (No.: 589221-K)

No, 93, Jalan Industri 3/3, Rawang Integrated Industrial Park, 48000 Rawang, Selangor Darul Ehsan, Malaysia.

+603 6094 2088 (Tel) +603 6099 2930 (Fax) sales@vitaltechnical.com

A MEMBER OF THE NIPPON PAINT GROUP

