



Formulated For The Professionals

VT-512 Multi Purpose Epoxy

Epoxy Adhesive

Multi Purpose Epoxy is a two-component epoxy designed to form a tough adhesive material that is resistant to weathering, fungus, seawater, decay, gasoline, alkali, and even certain acids. It is the original heavy-duty epoxy that is suitable for most conditions, and it allows longer working time for large assemblies with many components.

Applications:

It is specially formulated for heavy-duty bonding and repair applications, where increased strength, durability, and reliability are required. It works well on fiberglass, glass, wood, metal, concrete, and most plastics.

Available colour: Slightly yellowish clear liquid

Properties:

- Yellowish translucent cured colour
- 1:1 Mixing ratio by volume
- 2 hours working time
- 3 hours set time
- 8 hours to handling strength
- 18 hours to full strength



Item Code	Content	Carton Quantity
VT-512200	200 g Tin	50 Sets / Carton
VT-512450	450 g Tin	24 Sets / Carton
VT-512900	900 g Tin	12 Sets / Carton
VT-5121K8	1.80 kg Tin	6 Sets / Carton

Features

- High mechanical strength
- Excellent resistance to most chemicals
- Good weathering resistance
- High temperature resistance
- Does not shrink, chip, peel, or crack



RESIN | HARDENER



CURED



WOOD TABLE HOLE FILLING



WOOD FURNITURE



VITAL TECHNICAL SDN. BHD. (No.: 589221-K)

No, 93, Jalan Industri 3/3, Rawang Integrated Industrial Park, 48000 Rawang, Selangor Darul Ehsan, Malaysia.

+603 6094 2088 (Tel) +603 6099 2930 (Fax)

sales@vitaltechnical.com

A MEMBER OF THE NIPPON PAINT GROUP

