



Formulated For The Professionals
Adhesives & Sealants

VT-219 Fire Rated Silicone Sealant

100% Neutral Silicone Sealant

A one-component, gun grade neutral silicone sealant formulated to form elastomeric fire retardant seals in construction applications.

Applications:

Recommended for firestop sealing of interior and exterior building and construction joints, where a fire rating of up to 4 hours is required.

In addition, it may be used to seal vertical and horizontal joints between metals, masonry, concrete and other common construction materials.

Applicable Test / Standard:

1. BS EN 1366-4:2006 Fire Resistance Tests
2. AS 1530.4:2014 Methods for Fire Tests on Building Materials
3. ASTM C920 and ASTM C719, Type S, Grade NS, Class 50, NT, A
4. Low VOC - USEPA Method 24 under SCAQMD Rule 1168 & USEPA Method 310

Available colours: Matte Black and Matte Grey

| Item Code | Content | Carton Quantity |
|-----------|------------------|-----------------|
| VT-219 | 300 ml Cartridge | 24 / Carton |
| VT-219S | 600 ml Sausage | 20 / Carton |



Features

- Fire rating up to 4 hours
- ±50% movement capability
- Malaysian Fire & Rescue Department (Jabatan Bomba dan Penyelamat) certified
- Excellent weather and UV resistance
- Excellent adhesion to most substrates
- Matte finish



ACP FACADE



ACP WALL



UNDERGROUND TUNNEL JOINTS



VITAL TECHNICAL SDN. BHD. Co.No.: 200201021558 (589221-K)

+603 6094 2088 (Tel) +603 6099 2930 (Fax)

sales@vitaltechnical.com

www.vitaltechnical.com



A member of

