

	VITAL TECHNICAL SDN. BHD.	 
	Technical Data Sheet	
	VT-124 Wood and Parquet Adhesive	

Issuance date: 12/11/14

Revision date: 19/04/21

Revision No.: 21-01

Product Specification:

Appearance	: Viscous liquid
Colour	: Clear
Viscosity (Brookfield HA 6 @ 10rpm)	: 100e3 – 150e3 cps
Specific gravity	: 1.05 - 1.08
Solid content	: 36.00 % - 40.00 %
Wet tack	: Aggressive
Flammability	: Non-flammable
Shelf life	: 24 months
Features	: Clear colour : Excellent adhesion : Easy clean up

Packaging

Product Code	Content	Inner Box	Carton
VT-124	150 g tube	12	72



Product Description:

A water-based adhesive that is excellent for wood bonding application. It features quick setting, superior bonding strength and it bonds variety of porous substrates.

Applications:

Parquet flooring installation and repair, wood joining, PVC lamination, furniture repair, wooden frames, woodworking projects, etc. Notes: Not for outdoor use.

Directions:

1. Surfaces must be clean, dry and free of dirt, grease, oil or water.
2. Cut nozzle at 45° angle to desired bead-width. Squeeze tube and push adhesive ahead of nozzle to both surfaces.
3. Apply even pressure to consolidate the bond. Uncured adhesive can be cleaned up with damp cloth.
4. Replace cap after use and store in a cool, dry place.

Caution:

Safety data sheet available on request. For further health and safety information, consult the latest safety data sheet.

Storage:

Minimum of 24 months in tightly closed packing when stored in cool and dry place, below 30 °C.

Every endeavour has been made to ensure that the information given herein is true and reliable but it is given only for the guidance of our customers. The company cannot accept any responsibility for the loss or damage that may result from the use of the information, due to the possibility of variations of processing or working conditions and of workmanship outside our control. Users are advised to confirm suitability of this product by their own tests.

- END -