

	VITAL TECHNICAL SDN. BHD.	 
	Technical Data Sheet	
	VT-135 All Purpose Wood Filler	

Issuance date: 06/03/14

Revision date: 12/05/20

Revision No.: 20-01

Product Specification:			
Specific gravity	: 1.82 – 1.84		
Solid content	: 76.0 % – 78.0 %		
Features	: Ready to use		
	: Paintable		
	: Water clean up		
	: Specially formulated for woodwork and furniture applications		
Colors	: Natural, Brown, White, Cherry, Dark Walnut		
	: Mahogany, Jackwood and Oak		
Packaging	: 50 g tube card		
Product Code	Content	Inner Box	Carton
VT-135	50 g tube card	12	144



Product Description:

A ready-mixed, multipurpose filler formulated to repair surface imperfections, fill cracks and holes on wood. It is paintable with oil- and water-based paints. This water-based filler can be cleaned with water easily.

Applications:

Filling cracks and chips, repairing surface imperfections (dent, scratches, etc.) on woodwork, furniture, etc.

Directions:

1. Surfaces must be clean, dry and free of dirt, grease, oil or water.
2. Apply filler into cracks or holes, smooth with a scraper.
3. Allow to dry for 30 minutes in thin layer before sanding. Allow for longer drying times in thicker applications and colder weather.
4. Once completely cure, it can be sanded to a feathered edge for a perfect finish
5. Clean up with a wet cloth. Replace cap after use and store in cool, dry place.

Caution:

Safety data sheet available on request. For further health and safety information, consult the latest safety data sheet.

Storage:

- Store in a dry and cool place with temperature below 30 °C.
- Use within 12 months from date of production.

Every endeavour has been made to ensure that the information given herein is true and reliable but it is given only for the guidance of our customers. The company cannot accept any responsibility for the loss or damage that may result from the use of the information, due to the possibility of variations of processing or working conditions and of workmanship outside our control. Users are advised to confirm suitability of this product by their own tests.

- END -