

	VITAL TECHNICAL SDN. BHD.	 
	Technical Data Sheet	
	VT-152P/VT-152PBT/ VT-163 Vital Grey Pro RTV	

Issuance date: 31/03/08

Revision date: 22/10/2025

Revision No.: 25-01

VT-152P / VT-152PB / VT-163 Vital Grey Pro RTV

PHYSICAL STATE

Paste

ODOUR

Slight unique odour

COLOUR

Grey

TACK-FREE TIME

10 – 30 minutes

PACKAGING

32 g/tube carded
(144 packs/carton)
85 g/tube carded
(144 packs/carton)
85 g/tube boxed
(144 packs/carton)
300 g/cartridge
(24 cartridges/carton)

SHELF LIFE

24 months (tube)
12 months (cartridge)

STORAGE

Store in a dry and cool
place with temperature
below 30 °C

APPLICATION TEMPERATURE

-20 °C – 50 °C

DESCRIPTION



Vital Grey Pro RTV is specially designed for dealership warranty requirements that ensure extended drivetrain warranty compliance. It features fast-curing, sensor-safe, low odor, and non-corrosive formulation that meets performance specs of OE silicone gaskets. It forms reliable “formed-in-place” gaskets that resist cracking, shrinking, and migration caused by thermal cycling. It is permanently flexible and stable at between -80 °F to 625 °F (-62 °C to 330 °C) intermittent. It is also resistant against automotive fluids.

TECHNICAL DATA

Curing system	: Oxime
Specific gravity	: 1.04-1.08
Tensile at break	: ≥ 1.8 MPa
Elongation at break	: ≥ 280%
Shore A hardness	: 40-45

FEATURES

- High torque and vibration applications
- Guaranteed no leak
- Low odor and non-corrosive
- Excellent oil resistance

APPLICATION

- Rear valve covers, oil pans, timing covers, water pumps, thermostat housing, transmission pans etc.

APPLICATION DIRECTION

1. Surfaces must be clean, dry and free of dirt, grease, oil or water.
2. Puncture the tube with cap and install nozzle. Apply 2 – 4 mm bead to one surface only.
3. Fix the parts to be assembled before the tack-free time.
4. Uncured sealant can be cleaned up with mineral spirits.
5. Replace cap after use and store in a cool, dry place.

CAUTION

May cause an allergic skin reaction. Causes serious eye irritation. Avoid breathing dust/fumes/gas/mist/vapours/spray. Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. Specific treatment (see instructions on this label). Take off contaminated clothing and wash it before reuse.

LEGAL NOTES

Every endeavour has been made to ensure that the information given herein is true and reliable but it is given only for the guidance of our customers. The company cannot accept any responsibility for the loss or damage that may result from the use of the information, due to the possibility of variations of processing or working conditions and of workmanship outside our control. Users are advised to confirm suitability of this product by their own tests.