

Specially designed for dealership warranty requirements that ensure extended drivetrain warranty compliance. It features fast curing, sensor-safe, low odor, and non-corrosive formulation that meets performance specs of OE silicone gaskets. It forms reliable "formed-in-place" gaskets that resist cracking, shrinking, and migration caused by thermal cycling. It is permanently flexible and stable at between -80 °F to 625 °F (-62 °C to 330 °C). It is also resistant against automotive fluids.



Rear valve covers, oil pans, timing covers, water pumps, thermostat housing, transmission pans etc.



Item Code	Content	Inner Box	Carton Quantity
VT-152P38	38 g Tube Carded	12	144 / Carton
VT-152P85	85 g Tube Carded	12	144 / Carton
VT-152P100	100 g Tube Carded	12	144 / Carton
VT-163	400 g Cartridge	-	24 / Carton



- High torque and vibration applications
- Guaranteed no leak
- Low odor and non-corrosive
- Excellent oil resistance







GEARBOX



VITAL TECHNICAL SDN. BHD. (No.: 589221-K)

No, 93, Jalan Industri 3/3, Rawang Integrated Industrial Park, 48000 Rawang, Selangor Darul Ehsan, Malaysia.



() 🖂 sales@vita

sales@vitaltechnical.com







